

REMARKS

Favorable consideration of the patentability of the claims presented herein is respectfully solicited. It is believed that the petition for extension of time submitted herewith is sufficient to maintain the pendency of the instant application. If it is not, kindly consider this to be a petition for whatever time is needed to maintain this pendency. It is believed that the fee paid herewith is correct. However, if it is not, kindly credit or debit to appropriate amount in the undersigned attorneys' deposit account 07-1337.

Originally filed claims 1 – 46 have been canceled and their subject matter rewritten into a new set of claims 47 to 84 to clarify differences between the instant invention and prior art. An Information Disclosure Statement is being filed herewith to bring certain prior art to the examiner's attention. It is believed that new claims 47-84 are patentably distinct from the references applied by the examiner as well as the newly submitted references.

The specification has been amended and submitted herewith in amended form as a SUBSTITUTE SPECIFICATION. No prohibited new matter has been introduced by this SUBSTITUTE SPECIFICATION or by the newly submitted claims. It is urged that all of these amendments be entered.

This invention is directed to providing two television program guides to a typical television viewer. One of the guides has more detail than the other. Typically, as shown in claims 47 and 55, the present invention is characterized by a configuration in which different types/amounts of electronic program information are prepared to have different amounts (degrees) of detail. Each of these program informations is transmitted from a central transmitter to a plurality of receivers by causing it to accompany different "flows of broadcast data" type by type, respectively.

More specifically, for servicing a certain television (TV) channel, if such certain channel service is provided in a "flow of broadcast data" (e.g., a transport stream), highly detailed program information ("individual" in the specification) accompanies and is carried in the flow of

broadcast data (transport stream). This condition is exemplified for example in Fig. 2, in which, for example, "the certain channel service" is "ST100" and "the flow of broadcast data" is transport stream "TS1."

In contrast, program information having a low degree of detail ("general" in the specification) accompanies and is carried in a further flow of broadcast data (transport stream). This condition is also exemplified in Fig. 2, in which, for example, "the further flow of broadcast data" is illustrated by transport streams "TS2" and "TS3."

As a result, the channel service data ST100, having a large amount of program detail (individual), are transmitted in the transport stream TS1, but data transmitted in the other transports, TS2 and TS3, have a lesser amount of detail (general). This is because the broadcast of the service ST 100 is assigned to TS1, not to TS2 and TS3 (i.e., the ST100 is not serviced in TS2 and TS3).

The present invention is fundamentally directed to means for preparing electronic program information(s) and transmission of those informations from a central broadcasting transmitter to a plurality of receivers within the broadcast areas.

As should be clearly understood from the above comments, there is a distinctive difference between the present invention and the newly cited European patent EP-A-0721253 (referred to herein as D5). The "program description 830" and "program time information 835" of Fig. 8 of the D5 reference do not at all correspond to the "individual electronic program information (having a large amount of detail)" and the "general electronic program information" of the present invention. The D5 reference has nothing to do with whether or not program information is carried in a transport stream of a certain service as indicated by the program information.

In the D5 reference, "program description 830" and "program time information 835" are just used for two-dimensionally displaying a program guide for all the channels, in which the two axes are, respectively, channel numbers and broadcast times. That is, in the reference, the guide

information for all the channels (corresponding in intended function to the instant electronic program informations) has the same amount of detail for each channel, and has only one amount of detail for each channel, unlike the instant invention which provides for two (2) separate electronic program informations (guides) each having greater or lesser amounts of detail for each channels' offerings.

The D5 reference absolutely does not disclose nor teach nor suggest the concept provided by Applicants' invention; that is, transmission of different electronic program informations having different amounts of details for each program depending on which certain channel service is provided by which flow of broadcast data (transport stream). It will be clear that it has long been known to provide a guide to the offering(s) of TV channels both electronically and in print. It has not been known to provide two such complementary guides that disclose different details of the respective TV programs to the prospective audience. The claims of this application are limited to a system having such two guides with each having a different (greater or lesser) degree or amount of information about a specific TV program.

Like the D5 reference, the LaJoie et al. reference provides a technique for displaying channels lists and information (in some detail) for each program. Thus, the LaJoie et al. reference should be understood to disclose an electronic program information display technique that differs from that disclosed and claimed by Applicants in that;

in a certain transport stream (i.e., a certain flow of broadcast data), functioning as a certain transmission path and carrier, highly detailed program information is transmitted for a certain channel service whose program data are transmitted through the certain transport stream, and

program information of only a lesser degree of detail is transmitted for the remaining other channel services whose program data are not transmitted through the same certain transport stream.

The examiner's specific comments about the application of the disclosures of the several references to the originally filed claims have been carefully considered. Since these original claims have been canceled and rewritten as the new claims presented herein, it would not be


efficient to review these references and the examiner's application of the disclosures thereof to the present claims. Suffice it to say that the instant claims have features in them, as detailed above, which are not present in the references applied by the examiner or cited by the applicants. These distinctions are sufficient to warrant allowance of applicants' claims over the state of the prior art.

The examiner's comments on the informality of the drawings are hereby acknowledged. Since no claim in this application has been as yet allowed, it is requested that the submission of formal drawings be deferred pending allowance of a claim.

Therefore, it is respectfully submitted that the present application is in condition for allowance, except for the submission of formal drawings, and such action is solicited.

Respectfully submitted,

LOWE HAUPTMAN GILMAN & BERNER, LLP



Michael G. Gilman
Registration No. 19,114
Attorneys for the applicants

Customer No. 22429
1700 Diagonal Road,
Suite 300/310
Alexandria, Virginia 22314
(703) 684-1111 Voice
(703) 518-5499 Facsimile

Docket No. 041-2048

MGG/vgg

August 22, 2002



43-75007-35
Part of #10

MARKED-UP VERSION SHOWING CHANGES

SPECIFICATION

TITLE OF THE INVENTION

METHOD AND APPARATUS FOR PREPARING AND TRANSMITTING ELECTRONIC
5 PROGRAM INFORMATION AND APPARATUS FOR PRODUCING ELECTRONIC
PROGRAM GUIDE FROM THE ELECTRONIC PROGRAM INFORMATION

RECEIVED

AUG 27 2002

BACKGROUND OF THE INVENTION

Technology Center 2600

1. FIELD OF THE INVENTION:

10 The present invention relates to method and apparatus for
preparing and transmitting electronic program information
multiplexed with video and audio signals. Also, the present
invention relates to an apparatus for producing an electronic
program guide from the electronic program information
15 multiplexed with the video and audio signals.

2. DESCRIPTION OF THE RELATED ART:

In ^a digital satellite broadcasting, a video signal and an
audio signal are broadcasted from a ^{central} ~~center~~ station to a
plurality of terminals according to the Moving Picture Experts
20 Group 2 (MPEG2). In the MPEG2, video and audio signals are
multiplexed with each other ^{into} to a packet in the ^{central} ~~center~~ station,
and a plurality of packets are transmitted to each terminal in
^{the} a form of a transport stream (TS) representing a transmission
line. In this case, electronic program information prescribed
25 in the MPEG2 and DVB is transmitted with the video and audio

signals. The electronic program information includes both control information, used to reproduce the video and audio signals multiplexed with each other, and electronic program guide information, used to prepare an electronic program guide.

5 The electronic program ^{guide} information is described in a form of a section type table, and the section type is prescribed in ~~the~~ MPEG2 and DVB.

2.1. PREVIOUSLY PROPOSED ART:

Fig. 1 shows a configuration of a conventional digital
10 broadcasting system.

As shown in Fig. 1, a conventional digital broadcasting system 300 is composed of a ^{central} broadcasting station ~~center~~ system 301 and a plurality of ^{viewers'} ~~viewer's~~ terminals 302. In the ^{central} ~~center~~ broadcasting station ~~center~~ system 301, video and audio
15 signals of television programs are transmitted from a television program and electronic program information organizing system 312 to a video/audio stream producing system 313, and the video and audio signals are prepared as a video /audio stream in the system 313. Also, electronic program
20 scheduling information is transmitted from the television program and electronic program information organizing system 312 to an electronic program information preparing and transmitting system 314, and electronic program information, which is composed of program information, used to reproduce the
25 video and audio signals multiplexed with each other, and added

information, used to prepare ~~an~~ electronic program information, is prepared in the system 314. The video/audio stream produced in the system 313 and the electronic program information prepared in the system 314 are multiplexed with each other in a TS multiplexer and up-link system 315, the electronic program information multiplexed with the video/audio stream is received in an information receiving device (IRD) 302 ^{at} ~~of~~ each viewer's terminal (or a television set) through a satellite 316.

10 Also, ~~a~~ cipher key information is transmitted from a cipher key managing and producing system 317 to the IRD 302, and television program viewing information is returned from the IRD 302 to an accounting information collecting system 318 through a public switched telephone network (PSTN) 319.

15 2.2. PROBLEMS TO BE SOLVED BY THE INVENTION:

However, because an electronic program guide (called a common electronic program guide) of television programs provided by all broadcast service enterprisers is prepared in the conventional digital broadcasting system 300 and is displayed in each viewer's terminal 302, an electronic program guide (called an individual electronic program guide) of television programs provided by each broadcast service enterpriser cannot be prepared in the conventional digital broadcasting system 300.

25 Also, even though each broadcast service ~~enterpriser~~ ^{provider}

desires to provide various services for the viewers, because
the services provided by one broadcast service enterpriser ^{are} ~~is~~
~~set forth~~ ^{guided} in the electronic program guide in the same format as
those provided by another broadcast service ^{provider} ~~enterpriser~~,
5 features of the services provided by each broadcast service
^{provider} ~~enterpriser~~ cannot be realized by the viewer. ~~Therefore, a~~
~~high definition television program service can be guided at~~
~~the most.~~

10

SUMMARY OF THE INVENTION

A first object of the present invention is to provide, with
due consideration ^{of} ~~to~~ the drawbacks of such a conventional
digital broadcasting system, electronic program information
preparing and transmitting apparatus and method in which
15 electronic program information used for the preparation of an
individual electronic program guide and a common electronic
program guide is prepared and transmitted to a viewer while
effectively using a data transmission band.

Also, a second object of the present invention is to
20 provide an electronic program guide producing apparatus in
which an individual electronic program guide and a common
electronic program guide are produced according to the
electronic program information received from the electronic
program information preparing and transmitting apparatus and
25 displaying the individual electronic program guide and the

common electronic program guide while distinguishing the individual electronic program guide from the common electronic program guide.

The first object of the present invention is ^{achieved} provided by an
5 electronic program information preparing and transmitting apparatus, comprising:

electronic program information preparing means for preparing general electronic program information, in which electronic program information of a plurality of broadcast
10 service enterprisers is described on a general level, and ~~for~~ preparing individual electronic program information, in which the electronic program information of one broadcast service ~~provider~~ enterpriser is described on an individual level, for each broadcast service ~~enterpriser~~ ^{provider}; and

15 electronic program information transmitting means for transmitting the general electronic program information of ^{many} ~~the~~ broadcast service ^{providers} ~~enterprisers~~ and the individual electronic program information of ^{an individual} ~~the~~ broadcast service ^{provider} ~~enterprisers~~ prepared by the electronic program information preparing
20 means.

Also, the first object is achieved by an electronic program information preparing and transmitting method, comprising the steps of:

preparing general electronic program information described
25 on a general level from electronic program information of a

plurality of broadcast service ~~enterprisers~~ ^{providers};

preparing individual electronic program information described on an individual level from the electronic program information of one broadcast service ~~enterpriser~~ ^{provider} for each
5 broadcast service ~~enterpriser~~ ^{provider}; and

transmitting the general electronic program information of the ~~broadcast service enterprisers~~ ^{plurality of providers} and the individual electronic program information of ~~the broadcast service enterprisers~~ ^{an individual provider}.

10 In the above configuration and steps, general electronic program information described on a general level and individual electronic program information described on an individual level are prepared from electronic program information of ~~one broadcast service enterpriser~~ ^{each provider} by the
15 electronic program information preparing means for each broadcast service ~~enterpriser~~ ^{provider}. Thereafter, the pieces of general electronic program information corresponding to the ~~broadcast service enterprisers~~ ^{providers} and one piece of individual electronic program information corresponding to one broadcast
20 service ~~enterpriser~~ ^{provider} are transmitted to a viewer by the electronic program information transmitting means for each piece of individual electronic program information.

Accordingly, because individual electronic program information corresponding to all broadcast service
25 ~~enterprisers~~ ^{providers} is not prepared but individual electronic program

information corresponding to one broadcast service ^{provider} ~~enterpriser~~
is prepared and carried in a transport stream of the broadcast
service ^{provider} ~~enterpriser~~ for each broadcast service ^{provider} ~~enterpriser~~, ^{the}
data transmission band required for each broadcast service
5 ^{provider} ~~enterpriser~~ can be effectively used.

Also, because the viewer receives the piece of individual
electronic program information corresponding to each broadcast
service ^{provider} ~~enterpriser~~, an individual electronic program guide
described on ^{an} ~~the~~ individual level can be prepared on the
10 viewer side for each broadcast service ^{provider} ~~enterpriser~~. In
particular, in cases where the individual level corresponds to
a high ^{detail} ~~detailed~~ degree, the viewer can watch an individual
electronic program guide described ^{at a} ~~on the~~ high ^{detail} ~~detailed~~ degree,
for each broadcast service ^{provider} ~~enterpriser~~. Therefore, the viewer
15 can read detailed information ^{for} ~~of~~ each television program
listed in the individual electronic program guide.

Also, because the viewer receives the pieces of general
electronic program information corresponding to ^{each} ~~the~~ broadcast
service ^{provider} ~~enterprisers~~, a common electronic program guide
20 described on ^{an overall} ~~the~~ general level for the ^{plurality of} ~~the~~ broadcast service
^{providers} ~~enterprisers~~ can be prepared ^{at} ~~on~~ the viewer side. In
particular, in cases where the general level corresponds to a
low ^{detail} ~~detailed~~ degree, the viewer can watch a common electronic
program guide of the broadcast service ^{plurality of} ~~enterprisers~~ ^{providers} on the low
25 ^{of detail} ~~detailed~~ degree. Therefore, even though a large number of

television programs are listed in the common electronic program guide, the viewer can easily ^{obtain} realize information ^{about} of the television programs.

Also, because general electronic program information and
5 individual electronic program information are prepared from
electronic program information of ^{each} one broadcast service
^{provider} ~~enterpriser for each broadcast service enterpriser~~, each
broadcast service ^{provider} ~~enterpriser~~ is not required to prepare
general electronic program information of another broadcast
10 service ^{provider} ~~enterpriser~~.

It is ^{appropriate} ~~applicable~~ that ^a transport stream specifying
information ~~indicating a transport stream~~ be prepared by the
electronic program information preparing means for each piece
of individual electronic program information, and
15 the electronic program information transmitting means
comprise:

electronic program information outputting means for
outputting the pieces of general electronic program
information of the ^{plurality of} broadcast service ^{providers} ~~enterprisers~~, the pieces
20 of individual electronic program information of ^{each} the broadcast
service ^{providers} ~~enterprisers~~ and the pieces of transport stream
specifying information prepared by the electronic program
information preparing means; and

electronic program information multiplexing means for
25 multiplexing the pieces of general electronic program

information of the ^{plurality of} broadcast service ^{providers} enterprisers and one
piece of individual electronic program information of ^{one} ~~one~~
broadcast service ^{provider} ~~enterpriser~~ output by the electronic program
information outputting means to produce combined electronic
5 program information for each piece of individual electronic
program information, carrying each piece of combined
electronic program information in a transport stream, which is
indicated by the piece of transport stream specifying
information corresponding to the piece of individual
10 electronic program information multiplexed in the piece of
combined electronic program information, and transmitting the
pieces of combined electronic program information carried in
the transport streams to the viewer.

In the above configuration, each piece of combined
15 electronic program information is carried in a transport
stream indicated by the piece of transport stream specifying
information corresponding to the piece of individual
electronic program information. In other words, each piece of
combined electronic program information, in which the piece of
20 individual electronic program information of one broadcast
service ^{provider} ~~enterpriser~~ is multiplexed, is carried in the
transport stream of ^{that} the broadcast service ^{provider} ~~enterpriser~~.

Therefore, the individual electronic program information of
^{one} the broadcast service ^{provider} ~~enterpriser~~ can be displayed when a
25 viewer watches a television program of ^{that} the broadcast service

~~provider~~
enterpriser. Accordingly, there is no ~~probability~~ ^{possibility} that the individual electronic program information of a particular broadcast service ~~enterpriser~~ ^{provider} is erroneously displayed when the viewer watches a television program provided by another broadcast service ~~enterpriser~~ ^{provider} other than the particular ~~broadcast service enterpriser~~, so that ~~a trouble~~ ^{conflict} between broadcast service ~~enterprisers~~ ^{providers} can be avoided.

It is also applicable that one piece of individual electronic program information of a particular broadcast service ~~enterpriser~~ ^{provider} and pieces of general electronic program information of ^{many} broadcast service ~~enterprisers~~ ^{providers}, other than the particular broadcast service ~~enterpriser~~ ^{provider}, be transmitted to the viewer for each piece of individual electronic program information by the electronic program information transmitting means.

In the above configuration, ^{the} general electronic program information of each broadcast service ~~enterpriser~~ ^{provider} is not transmitted to the viewer with individual electronic program information of the broadcast service ~~enterpriser~~ ^{provider}. Therefore, electronic program information of each broadcast service ~~enterpriser~~ ^{provider} is not transmitted in duplicate.

It is also applicable that the electronic program information preparing means comprise:

common electronic program information preparing means for preparing common electronic program information common to the

pieces of electronic program information of the broadcast
service ^{providers} ~~enterprisers~~ from the pieces of electronic program
information of ^{each} ~~the~~ broadcast service ^{provider} ~~enterprisers~~;

- non-common electronic program information preparing means
- 5 for preparing ^a first non-common electronic program information
not common to the ^{plurality of} ~~broadcast service enterprisers~~ on the ~~an~~
individual level from the electronic program information of
^{each} ~~one~~ broadcast service ^{provider} ~~enterpriser~~ for each broadcast service
~~enterpriser~~ and preparing ^a second non-common electronic program
10 information not common to the ^{plurality of} ~~broadcast service enterprisers~~ ^{providers}
on the ^a general level from the electronic program information
^{each} ~~of one~~ broadcast service ^{provider} ~~enterpriser~~ for each broadcast
~~service enterpriser~~, and
- the electronic program information transmitting means
- 15 comprises:

- electronic program information multiplexing means for
multiplexing the common electronic program information
prepared by the common electronic program information
preparing means, one piece of ^a first non-common electronic
20 program information of a particular broadcast service
^{provider} ~~enterpriser~~ prepared by the non-common electronic program
information preparing means and pieces of ^a second non-common
electronic program information of broadcast service
^{providers} ~~enterprisers~~, other than the particular broadcast service
^{provider} ~~enterpriser~~ with each other to produce multiplexed electronic
- 25

program information for each particular broadcast service

~~provider~~
enterpriser; and

multiplexed electronic program information transmitting
means for transmitting the multiplexed electronic program

5 information produced by the electronic program information
multiplexing means to the viewer for each particular broadcast
service ~~enterpriser~~ ^{provider}.

In the above configuration, ~~common~~ electronic program
information common to the pieces of electronic program
10 information of the ^{plurality of} broadcast service ~~enterprisers~~ ^{providers} is prepared
from the pieces of electronic program information of ^{each} the
broadcast service ~~enterprisers~~ ^{provider} in the common electronic
program information preparing means. Accordingly, each
particular broadcast service ~~enterpriser~~ ^{provider} is not required to
15 prepare the common electronic program information.

It is also preferred that a plurality of channel services
be listed in the general electronic program information or in
the individual electronic program information of one broadcast
service ~~enterpriser~~ ^{provider} prepared by the electronic program
20 information preparing means, and service specifying
information indicating ~~the specifying of~~ a particular channel
service is arranged in the general electronic program
information or the individual electronic program information
of the broadcast service ~~enterpriser~~ ^{provider} to automatically select
25 the particular channel service from the channel services in

^{that} cases where ~~the~~ broadcast service ^{provider} ~~enterpriser~~ is selected.

In the above configuration, even though each broadcast service ^{provider} ~~enterpriser~~ provides a plurality of channel services, when a viewer selects one broadcast service ^{provider} ~~enterpriser~~, ^{that} ~~a~~ the particular channel service of the broadcast service ^{provider} ~~enterpriser~~ is automatically specified according to the service specifying information. Accordingly, each broadcast service ^{provider} ~~enterpriser~~ can make the viewer automatically watch a television program of the particular channel service recommended by ^{that} the broadcast service ^{provider} ~~enterpriser~~.

It is also preferred that pieces of information of a plurality of television programs be described in the individual electronic program information or the general electronic program information and program link describing information indicating that an actual television program actually broadcasted ~~//~~ is the same as one or more virtual television programs not actually broadcasted ~~//~~ be arranged in the individual electronic program information or the general electronic program information.

In the above configuration, in cases where a high definition television (HDTV) program is provided, because the HDTV program extends over a plurality of television channels, the HDTV program of one television channel is actually broadcasted ~~//~~ as an actual television program, and the HDTV program of the other television channels is not actually

broadcasted~~ed~~ as a virtual television program. In this case,
program link describing information (or event link *describing*
information) arranged in the general electronic program
information or the individual electronic program information
5 indicates that the virtual television programs are the same as
the actual television program.

It is also preferred that pieces of information of one or
more television programs are listed in the general electronic
program information or the individual electronic program
10 information of each broadcast service *provider* ~~enterpriser~~ prepared by
the electronic program information preparing means and a
transmission bandwidth be described as the information *for* ~~of~~ each
television program.

In the above configuration, a transmission bandwidth
15 indicating a display quality ¹⁵ ~~be~~ described as the information
of each television program in the general electronic program
information or the individual electronic program information.
Therefore, the viewer can select one of the television
programs according to the transmission bandwidth.

20 It is also preferred that information of one broadcast
service *provider* ~~enterpriser~~, information of a broadcasting schedule
and information of a television channel ¹⁵ ~~be~~ described as the
information of each television program to produce a three-
dimensional electronic program guide in which a display width
25 of each television program is proportional to the transmission

bandwidth of the television program.

In the above configuration, information of one broadcast service ~~enterpriser~~^{provider}, information of a broadcasting schedule and information of a television channel are described as the information ~~of~~^{for} each television program. Therefore, a three-dimensional electronic program guide, in which a display width of each television program is proportional to the transmission bandwidth of the television program, can be produced.

Accordingly, the viewer can easily select a television program while watching the three-dimensional electronic program guide.

It is also preferred that one or more main channel services and one or more sub-channel services ~~subordinate~~^{that are} to one main channel service, be hierarchically listed in the general electronic program information or in the individual electronic program information of each broadcast service ~~enterpriser~~^{provider} prepared by the electronic program information preparing means.

It is also preferred that one or more main television programs and one or more ~~sub~~^{that are} television programs subordinate to ~~one~~^{the} main television program are hierarchically listed in the general electronic program information or the individual electronic program information of each broadcast service ~~enterpriser~~^{provider} prepared by the electronic program information preparing means.

In the above configuration, the main channel services (or

the main television programs) and the sub-channel services (or the sub-television programs) are hierarchically listed in the general electronic program information or in the individual electronic program information. Therefore, even though a large number of channel services (or television programs) are provided by one broadcast service ~~enterpriser~~ ^{provider}, an electronic program guide, in which the channel services (or television programs) are hierarchically arranged, can be easily produced. Accordingly, the viewer can easily select one channel service (or one television program) from the channel services (or television programs) of the electronic program guide.

It is also preferred that the general electronic program information including information of the main channel services be carried in all transport streams and the individual electronic program information including information of the sub-channel services be carried in a particular transport stream in which television programs of the sub-channel services are actually carried.

In the above configuration, because information of the main channel services is carried in all transport streams of all broadcast service ~~enterprisers~~ ^{providers}, the information of the main channel services arranged in a common electronic program table can be displayed regardless of ~~any~~ ^{which} broadcast service ~~enterpriser~~ ^{provider} is selected by the viewer. Also, because information of the sub-channel services is carried in a particular

transport stream in which television programs of the sub-channel services are actually carried, when the viewer selects a particular broadcast service ~~enterpriser~~ ^{provider} corresponding to the sub-channel services, the information of the sub-channel services arranged in an individual electronic program table
5 can be displayed.

It is also preferred that television programs provided by a particular broadcast service ~~enterpriser~~ ^{provider} be carried in a plurality of particular transport streams, television programs
10 of the sub-channel services be carried in one particular transport stream, the general electronic program information including information of the main channel services be carried in all transport streams and the individual electronic program information including information of the sub-channel services
15 be carried in each of the particular transport streams.

In the above configuration, in cases where a plurality of particular transport streams correspond to a plurality of channel services of a particular broadcast service ~~enterpriser~~ ^{provider}, information of the sub-channel services provided
20 by the particular broadcast service ~~enterpriser~~ ^{provider} is carried ~~in~~ by each of the particular transport streams. Therefore, even though the viewer selects ~~any of~~ the channel services of the particular broadcast service ~~enterpriser~~ ^{provider}, the information of the sub-channel services arranged in an individual electronic
25 program table can be displayed.

The second object of the present invention is ^{achieved} provided by
an electronic program guide producing apparatus, comprising:

electronic program information receiving means for
receiving electronic program information of a plurality of
5 broadcast service ~~enterprisers~~ ^{providers};

common electronic program guide producing means for
producing a common electronic program guide of channel
services provided by ^{a plurality of} the broadcast service ~~enterprisers~~ ^{providers} from
the electronic program information of ^{each} the broadcast service
10 ~~enterprisers~~ ^{provider} received by the electronic program information
receiving means; and

individual electronic program guide producing means for
producing an individual electronic program guide of channel
services ^{made available} provided by one broadcast service ~~enterpriser~~ ^{provider} from
15 the electronic program information of ^{that} the broadcast service
~~enterpriser~~ ^{provider} received by the electronic program information
receiving means for ^{all} each broadcast service ~~enterpriser~~ ^{providers}.

In the above configuration, a common electronic program
guide of channel services provided by the broadcast service
20 ~~enterprisers~~ ^{providers} is produced from the pieces of general electronic
program information of ^{each} the broadcast service ~~enterprisers~~ ^{provider}, and
an individual electronic program guide of channel services
provided by each broadcast service ~~enterpriser~~ ^{provider} is produced
from the individual electronic program information of ^{the} ~~each~~
25 broadcast service ~~enterpriser~~ ^{provider}.

Accordingly, the viewer can watch the common electronic program guide displayed on a displaying unit. Also, the viewer can watch the individual electronic program guide displayed on the displaying unit.

- 5 Also, because the individual electronic program guide of all broadcast service ~~enterprisers~~ ^{providers} is not produced, but the individual electronic program guide of each broadcast service ~~enterpriser~~ ^{provider} is produced and displayed with a television program of ~~the~~ ^{that} broadcast service ~~enterpriser~~ ^{provider}, ~~a~~ ^{the} data
- 10 transmission band required for the individual electronic program guide displayed can be effectively used.

It is preferred that the electronic program guide producing apparatus further comprise:

- displaying means for displaying a television program of a
- 15 channel service provided by a particular broadcast service ~~enterpriser~~ ^{provider} selected from the ~~broadcast service enterprisers~~ ^{plurality of providers},
- ~~displaying~~ the common electronic program guide produced by the common electronic program guide producing means regardless of the particular broadcast service ~~enterpriser~~ ^{provider selected}, and ~~displaying~~ a
- 20 particular individual electronic program guide of the particular broadcast service ~~enterpriser~~ ^{provider} produced by the individual electronic program guide producing means while displaying the television program of the channel service provided by the ~~particular broadcast service enterpriser~~ ^{selected provider}.

- 25 In the above configuration, the common electronic program

guide is displayed by the displaying means regardless of the
broadcast service ~~enterpriser~~ ^{provider} of the television program
displayed by the displaying means. Also, the particular
individual electronic program guide of the particular
5 broadcast service ~~enterpriser~~ ^{provider} is displayed only when ~~one~~ ^a
television program of the channel service provided by ~~the~~ ^{that}
particular broadcast service ~~enterpriser~~ ^{provider} is displayed.

Accordingly, the common electronic program guide can be
displayed any time. Also, the individual electronic program
10 guide of each broadcast service ~~enterpriser~~ ^{provider} can be displayed
when a television program provided by ~~the~~ ^{that} broadcast service
~~enterpriser~~ ^{provider} is displayed. Therefore, there is no probability
that an individual electronic program guide of a broadcast
service ~~enterpriser~~ ^{provider}, other than the particular broadcast
15 service ~~enterpriser~~ ^{provider} providing the television program currently
displayed by the displaying means, is erroneously displayed, so
that a ~~trouble~~ ^{conflict} between broadcast service enterprisers can be
avoided.

It is also preferred that a plurality of channel services
20 be listed in the electronic program information of one
broadcast service ~~enterpriser~~ ^{provider} received by the electronic
program information receiving means, service specifying
information indicating ~~the~~ ~~specifying~~ of a particular channel
service selected from the channel services ~~be~~ arranged in the
25 electronic program information, and a television program of

the particular channel service of the broadcast service
~~provider~~ enterpriser be automatically displayed by the displaying means
in cases where the viewer selects ~~the~~ ^{that} broadcast service
~~provider~~ enterpriser.

- 5 In the above configuration, even though each broadcast
service ~~enterpriser~~ ^{provider} provides a plurality of channel services,
when a viewer selects ~~one~~ ^{a particular} broadcast service ~~enterpriser~~ ^{provider}, ~~the~~ ^{that}
particular channel service of the broadcast service
~~enterpriser~~ ^{provider} is automatically specified according to the
10 service specifying information. Accordingly, each broadcast
service ~~enterpriser~~ ^{provider} can make the viewer automatically watch a
television program of the particular channel service
recommended by ~~the~~ ^{that} broadcast service ~~enterpriser~~ ^{provider}.

- It is also preferred that a plurality of channel services
15 be listed in one individual electronic program guide produced
by the individual electronic program guide producing means or
in the common electronic program guide produced by the common
electronic program guide producing means. ~~A~~ ^A viewer attribute
~~be~~ ^{is} arranged as information of each channel service of the
20 individual electronic program guide or the common electronic
program guide, and a television program of a particular
channel service of ~~the~~ ^{a particular} broadcast service ~~enterpriser~~ ^{provider} ~~be~~ ^{is}
automatically displayed by the displaying means in cases where
the viewer attribute ~~of the~~ ^{identifying a} particular channel service agrees
~~with an attribute of the viewer~~ ^{identified by} ~~in the individual electronic~~ ^{specified}
25 with an attribute ~~of the viewer~~ ^{identified by} in the individual electronic

program guide or the common electronic program guide.

In the above configuration, each broadcast service
5 ~~enterpriser~~ ^{provider} provides a plurality of channel services, and a
viewer attribute is arranged ^{identifying} as information of each channel
service of the individual electronic program guide or the
common electronic program guide. Therefore, when a viewer
selects ^{a particular} ~~one~~ broadcast service ^{provider} ~~enterpriser~~, a particular
channel service, of which the ~~viewer~~ attribute agrees with an
attribute of the viewer in the individual electronic program
10 guide or the common electronic program guide, is automatically
selected, and a television program of the particular channel
service of ^{that} ~~the~~ broadcast service ^{provider} ~~enterpriser~~ is displayed.
Accordingly, each broadcast service ^{provider} ~~enterpriser~~ can make the
viewer automatically watch the television program of the
15 particular channel service recommended by ^{that} ~~the~~ broadcast
service ^{provider} ~~enterpriser~~.

It is also preferred that a plurality of channel services
be listed in one individual electronic program guide produced
by the individual electronic program guide producing means or
20 in the common electronic program guide produced by the common
electronic program guide producing means. ^{It} ~~A~~ genre ^{is} ~~be~~ arranged
as information of each channel service of the individual
electronic program guide or the common electronic program
guide, and a television program of a particular channel
25 service of ^{a particular} ~~the~~ broadcast service ^{provider} ~~enterpriser~~ ^{is} ~~be~~ automatically

displayed by the displaying means in cases where the genre of the particular channel service agrees with a viewer's favorite genre in the individual electronic program guide or the common electronic program guide.

5 In the above configuration, each broadcast service ~~enterprise~~^{provider} provides a plurality of channel services, and a genre is arranged ~~as~~^{based on} information ~~of~~^{for} each channel service of the individual electronic program guide or the common electronic program guide. Therefore, when a viewer selects one
10 broadcast service ~~enterprise~~^{provider}, a particular channel service, of which the genre agrees with a viewer's favorite genre in the individual electronic program guide or the common electronic program guide of the broadcast service ~~enterprise~~^{provider}, is automatically selected, and a television program of the
15 particular channel service of ~~the~~^{that} broadcast service ~~enterprise~~^{provider} is displayed. Accordingly, each broadcast service ~~enterprise~~^{provider} can make the viewer automatically watch the television program of the particular channel service recommended by ~~the~~^{that} broadcast service ~~enterprise~~^{provider}.

20 It is also preferred that pieces of information of a plurality of television programs be described in one individual electronic program guide produced by the individual electronic program guide producing means or in the common electronic program guide produced by the common electronic
25 program guide producing means, program link describing

information indicating that an actual television program
actually broadcasted~~/~~ is the same as one or more virtual
television programs not actually broadcasted~~/~~ be arranged in
the individual electronic program guide or the common
5 electronic program guide, and the individual electronic
program guide or the common electronic program information be
displayed by the displaying means.

In the above configuration, in cases where a high
definition television (HDTV) program is provided, because the
10 HDTV program extends over a plurality of television channels,
the HDTV program of one television channel is actually
broadcasted~~/~~ as an actual television program, and the HDTV
program of the other television channels is not actually
broadcasted~~/~~ as a virtual television program. In this case,
15 program link describing information is described in the
individual electronic program guide or the common electronic
program guide to indicate that the virtual television programs
are the same as the actual television program. Therefore, the
viewer can recognize the virtual television programs, and the
20 viewer can select the HDTV program without any trouble.

It is also preferred that information of a particular
program extending over a plurality of television channels be
described in one individual electronic program guide produced
by the individual electronic program guide producing means or
25 in the common electronic program guide produced by the common

electronic program guide producing means and the information
of the particular program ¹³ ~~be~~ displayed by the displaying means
~~as~~ ¹⁴ the individual electronic program guide or the common
electronic program guide.

5 In the above configuration, even though a particular
program, extending over a plurality of television channels, is
broadcast~~ed~~, information of the particular program is
displayed ¹⁵ ~~as~~ the individual electronic program guide.
Therefore, the viewer can recognize the particular program
10 extending over ^{a plurality of} the television channels by watching the
individual electronic program guide.

It is also preferred that information of a particular
television program extending over a plurality of television
channels be described in one individual electronic program
15 guide produced by the individual electronic program guide
producing means or the common electronic program guide
produced by the common electronic program guide producing
means, the information of the particular television program be
described in each television channel of the individual
20 electronic program guide or the common electronic program
guide, the information of the particular television program
described in each television channel be displayed by the
displaying means as the individual electronic program guide or
the common electronic program guide, and the selection of the
25 particular television program be visually indicated ^{on} ~~in~~ each

television channel in cases where the particular television program of one television channel is selected.

In the above configuration, even though a particular program extending over a plurality of television channels is broadcasted, information of the particular television program is described in each television channel and is displayed as the individual electronic program guide or the common electronic program guide. Thereafter, when the viewer selects the particular television program of one television channel, the selection of the particular television program is visually indicated in each television channel. Therefore, the viewer can easily recognize the television channels corresponding to the particular program.

It is also preferred that display quality information be described as information of each television program in one individual electronic program guide produced by the individual electronic program guide producing means or in the common electronic program guide produced by the common electronic program guide producing means to indicate a display quality of the television program, and pieces of information of the television programs ^{are} ~~be~~ displayed by the displaying means as the individual electronic program guide or the common electronic program guide to indicate the display quality of each television program according to the display quality information of the television program.

In the above configuration, display quality information, indicating ^{the} ~~a~~ display quality of each television program, is described as information of the television program in ~~one~~ ^{the} individual electronic program guide or the common electronic program guide, ~~and the display quality information of the television programs are displayed.~~ Therefore, the viewer can select one of the television programs while referring ^{to} ~~the~~ display quality information.

It is also preferred that information of one broadcast service ~~enterpriser~~ ^{provider}, information of a schedule and information of a television channel be described as information ^{relative to} ~~of~~ each television program in one individual electronic program guide produced by the individual electronic program guide producing means or in the common electronic program guide produced by the common electronic program guide producing means, a transmission bandwidth be described as information ^{related to} ~~of~~ each television program in the individual electronic program guide or the common electronic program guide, and a three-dimensional electronic program guide composed of three components of the broadcast service ~~enterpriser~~ ^{provider}, the schedule and the television channel be displayed by the displaying means on condition that ^{the} ~~a~~ display width of each television program in the three-dimensional electronic program guide is proportional to the transmission bandwidth of the television program.

In the above configuration, information of one broadcast service ~~enterpriser~~ ^{provider}, information of a broadcasting schedule and information of a television channel are described as the information of each television program in one individual

5 electronic program guide, a transmission bandwidth indicating ~~the~~ ^{display} quality of each television program is described as information ~~of~~ ^{related to} the television program in the individual electronic program guide or in the common electronic program guide, and a three-dimensional electronic program guide, in
10 which ~~the~~ ^{display} width of each television program is proportional to the transmission bandwidth of the television program, is displayed. Accordingly, the viewer can easily select a television program while watching the three-dimension-
al electronic program guide.

15 It is also preferred that information of television programs be described in one individual electronic program guide produced by the individual electronic program guide producing means or in the common electronic program guide produced by the common electronic program guide producing
20 means, the information of the television programs be displayed by the displaying means as the individual electronic program guide or the common electronic program guide while displaying a television program of one television channel, and the electronic program guide producing apparatus, further
25 comprise:

television channel changing means for changing a television program of a first television channel to a television program of a second television channel in cases where the television program of the first television channel has no relationship with the television program of the second television channel and changing the television program of the first television channel to a television program of a third television channel in cases where the television program of the first television channel refers to the information of the television program of the second television channel, the television program of the second television channel refers to the information of the television program of the first television channel or the television programs of the first and second television channels refers to the information of a television program of one television channel.

In the above configuration, a plurality of television channels are normally selected by the television channel changing means one after another in the predetermined order. However, in cases where the television program of a first television channel ~~has relationship with~~ ^{is related to} the television program of a second television channel, the change from the first television channel to the second television channel is not performed. In detail, in cases where the television program of the first television channel refers to the information of the television program of the second television

channel, the television program of the second television
channel refers to the information of the television program of
the first television channel or the television programs of the
first and second television channels refers to the information
5 of a television program of one television channel, the second
television channel is not selected, but a third television
channel is selected.

Accordingly, because the first television channel is
automatically changed to the third television channel, the
10 viewer is not required to select the third television channel
having no relationship with the television program of the
first television channel by repeatedly operating the
television channel changing means. Therefore, the viewer can
rapidly select a next television program having no
15 relationship with the television program of a previously-
selected television channel.

It is also preferred that channel identifying information
indicating the second television channel or the third
television channel changed by the television channel changing
20 means and one or more fourth television channels be displayed
in cases where the second television channel or the third
television channel and the fourth television channels refer to
information of the same television channel, and channel
identifying information indicating the second television
25 channel or the third television channel changed by the

television channel changing means and one or more fifth television channels be displayed in cases where the fifth television channels refer to information of the second television channel or information of the third television
5 channel.

In the above configuration, the first television channel is changed to the second television channel (or the third television channel) by the television channel changing means. In cases where the second television channel (or the third
10 television channel) and one or more fourth television channels refer to information of one television channel, channel identifying information indicating the second television channel (or the third television channel) and the fourth television channels is displayed. Also, in cases where one or
15 more fifth television channels refer to information of the second television channel (or information of the third television channel), channel identifying information indicating the second television channel (or the third television channel) and the fifth television channels is
20 displayed.

It is also preferred that information of one or more main channel services and information of one or more sub-channel services subordinate to one main channel service be hierarchically described in one individual electronic program
25 guide produced by the individual electronic program guide

producing means or in the common electronic program guide produced by the common electronic program guide producing means, and the information of the main channel services and the information of the sub-channel services hierarchically
5 described be displayed by the displaying means as the individual electronic program guide or the common electronic program guide.

It is also preferred that information of one or more main television programs and information of one or more ~~sub-~~
10 television programs subordinate to one main television program be hierarchically described in one individual electronic program guide produced by the individual electronic program guide producing means or the common electronic program guide produced by the common electronic program guide producing
15 means, and the information of the main television programs and the information of the sub-television programs hierarchically described be displayed by the displaying means as the individual electronic program guide or the common electronic program guide.

20 In the above configuration, information of the main channel services (or the main television programs) and information of the sub-channel services (or the sub-television programs) are hierarchically described in one individual electronic program guide or the common electronic program guide and are
25 displayed. Therefore, even though a large number of channel

services (or television programs) are provided by one
broadcast service ~~enterpriser~~^{provider}, an electronic program guide, in
which the channel services (or television programs) are
hierarchically arranged, can be easily produced. Accordingly,
5 the viewer can easily select one channel service (or one
television program) from the channel services (or television
programs) of the electronic program guide.

It is also preferred that information of a main television
program and information of one or more sub-television programs,
10 subordinate to the main television program, be hierarchically
described in one individual electronic program guide produced
by the individual electronic program guide producing means or
the common electronic program guide produced by the common
electronic program guide producing means, the information of
15 the main television programs be displayed by the displaying
means as the individual electronic program guide, and the
information of the sub-television programs be displayed by the
displaying means as the individual electronic program guide or
the common electronic program guide in cases where the main
20 television program or a channel service of the main television
program described in the information of the main television
programs is selected.

In the above configuration, when information of the main
television program or a channel service of the main television
25 program described in the information of the main television

programs is selected by the viewer, the information of the
~~sub~~-television programs subordinate to the main television
program is automatically displayed. Therefore, the viewer is
not required to ^{manually} select each of the sub-television programs.

5 It is also preferred that information of a main television
program and information of one or more ~~sub~~-television programs
subordinate to the main television program be hierarchically
described in one individual electronic program guide produced
by the individual electronic program guide producing means or
10 the common electronic program guide produced by the common
electronic program guide producing means, a viewer attribute
be described as information ^{related to} of each sub-television program,
and a particular sub-television program be automatically
displayed by the displaying means, on condition that the
15 viewer attribute described as the information of the
particular sub-television program agrees with an attribute ^{identified} of ^{by}
the viewer, in cases where the viewer selects the main
television program.

In the above configuration, when the viewer selects the
20 information of the main television program, a particular sub-
television program is selected from among the sub-television
programs subordinate to the main television program on
condition that the viewer attribute of the particular sub-
television program agrees with an attribute ^{selected by} of the viewer, and
25 the particular sub-television program is automatically

displayed. Therefore, the viewer can easily watch his most favorite television program.

It is also preferred that information of a main television program and information of one or more sub-television programs subordinate to the main television program be hierarchically described in one individual electronic program guide produced by the individual electronic program guide producing means or the common electronic program guide produced by the common electronic program guide producing means, a genre be described as information of each sub-television program, and a particular sub-television program be automatically displayed by the displaying means, on condition that the genre described as the information of the particular sub-television program agrees with a viewer favorite genre, in cases where the viewer selects the main television program.

In the above configuration, when the viewer selects the information of the main television program, a particular sub-television program is selected from among the sub-television programs subordinate to the main television program on condition that the genre of the particular sub-television program agrees with a viewer ^{selected} favorite genre, and the particular sub-television program is automatically displayed. Therefore, the viewer can easily watch his most favorite television program.

BRIEF DESCRIPTION OF THE DRAWINGS

The objects, features and advantages of the present invention will be apparent from the following description taken in conjunction with the accompanying drawings, in which:

5 Fig. 1 shows a configuration of a conventional digital broadcasting system composed of a broadcasting station center system and a plurality of viewer's terminals;

Fig. 2 is an explanatory view showing a total configuration of an electronic program information preparing and
10 transmitting apparatus according to a first embodiment of the present invention;

Fig. 3 shows an example of a service description table (SDT) of a channel service ST100 described on an individual level and an example of an event information table (EIT) of
15 the channel service ST100 described on the individual level;

Fig. 4 shows an example of a service description table (SDT) of a channel service ST100 described on a general level and an example of an event information table (EIT) of the channel service ST100 described on the general level;

20 Fig. 5 shows an example of a common electronic program guide of television programs provided by all broadcast service
providers
enterprisers;

Fig. 6 shows an example of an individual electronic program guide of television programs provided by ^{an individual} ~~a~~ broadcast service
provider
25 enterpriser;

Fig. 7 is an explanatory view showing a total configuration of an electronic program information preparing and transmitting apparatus according to a second embodiment of the present invention;

5 Fig. 8 is an explanatory view showing a total configuration of an electronic program information preparing and transmitting apparatus according to a third embodiment of the present invention;

Fig. 9 is a block diagram of an electronic program
10 information receiving terminal including an electronic program guide producing apparatus according to a fourth embodiment of the present invention;

Fig. 10 shows a bouquet association table (BAT) and a network information table (NIT) in case of digital video
15 broadcasting (DVB) of European digital broadcast standards;

Fig. 11 shows a program association table (PAT) and a program map table (PMT) in case of MPEG2;

Fig. 12 shows an event information table (EIT) and a service description table (SDT) in case of digital video
20 broadcasting (DVB) of European digital broadcast standards;

Fig. 13 shows one or more channel services, general electronic program information and non-common electronic program information transmitted to the receiving terminal apparatus including an electronic program information
25 receiving apparatus as each transport stream;

Fig. 14 shows an example of an individual electronic program guide displayed according to the fourth embodiment;

Fig. 15 is a block diagram of an electronic program information receiving apparatus including an electronic program guide producing terminal according to a fifth embodiment of the present invention;

Fig. 16 shows two bouquet association tables (BATs) according to the fifth embodiment of the present invention;

Fig. 17 shows a television channel automatic selection, in which a television channel of a broadcasting station "Fujisan" is automatically changed to a particular television channel of a broadcasting station "Japan TV" according to a default flag attached to a channel service of the broadcasting station "Japan TV" when a viewer selects the broadcasting station "Japan TV", according to the fifth embodiment;

Fig. 18 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a sixth embodiment of the present invention;

Fig. 19 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a seventh embodiment of the present invention;

Fig. 20 shows an event information table EIT, in which event link information corresponding to an actual television

program actually broadcasted is not described in a column of the event link information and two event information tables EIT in which event link information corresponding to a virtual television program not actually broadcasted is described in a column of the event link information, according to the seventh embodiment

Fig. 21 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to an eighth embodiment of the present invention;

Fig. 22 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a ninth embodiment of the present invention;

Fig. 23 shows a television program table, in which information of an HDTV program extending over three television channels adjacent to each other is described, according to the ninth embodiment;

Fig. 24 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a tenth embodiment of the present invention;

Fig. 25 shows a television program table, in which information of an HDTV program extending over three television channels separately positioned is highlighted, according to

the tenth embodiment;

Fig. 26 shows a plurality of event information tables EIT,
in which bandwidth information is described for each
television program, according to an eleventh embodiment of the
5 present invention;

Fig. 27 is a block diagram of an electronic program
information receiving terminal including an electronic program
guide producing apparatus according to the eleventh embodiment
of the present invention;

10 Fig. 28 shows a television program table, in which a display
width for information of one television program is set for
each television program, according to the eleventh embodiment;

Fig. 29 shows an electronic program table, in which a
display width for television program information is set for
15 each television channel, according to a modification of the
eleventh embodiment;

Fig. 30 shows a correspondence table indicating the
correspondence between each channel service type and one
display width according to a modification of the eleventh
20 embodiment;

Fig. 31 is a block diagram of an electronic program
information receiving terminal including an electronic program
guide producing apparatus according to a twelfth embodiment of
the present invention;

25 Fig. 32 shows an example of a three-dimensional electronic

program guide according to the twelfth embodiment;

Fig. 33 shows an example of an electronic program guide according to the twelfth embodiment;

Fig. 34 shows a plurality of television programs displayed
5 on a displaying unit one after another according to the twelfth embodiment;

Fig. 35 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a thirteenth embodiment
10 of the present invention;

Fig. 36 shows a plurality of television programs displayed on a displaying unit one after another according to the thirteenth embodiment;

Fig. 37 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a fourteenth embodiment
15 of the present invention;

Fig. 38 shows an example of main channel services and sub-channel services according to a fifteenth embodiment of the
20 present invention;

Fig. 39 shows an example of transport streams in which a plurality of channel services are carried;

Fig. 40 shows an example of a service description table SDT of main channel services;

25 Fig. 41 shows an example of a service description table SDT

of main channel services and sub-channel services;

Fig. 42 shows an example of an event information table EIT of a main channel service;

Fig. 43 shows an example of an event information table EIT
5 of another main channel service;

Fig. 44 shows an example of event information tables EIT of sub-channel services;

Fig. 45 is a block diagram of an electronic program
information receiving terminal including an electronic program
10 guide producing apparatus according to the fifteenth
embodiment;

Fig. 46 shows an example of transport streams in which a
plurality of channel services and electronic program
information of the channel services are carried, according to
15 a sixteenth embodiment of the present invention;

Fig. 47 is a block diagram of an electronic program
information receiving terminal including an electronic program
guide producing apparatus according to the sixteenth
embodiment;

20 Fig. 48 shows an example of transport streams in which a
plurality of channel services and electronic program
information of the channel services are carried, according to
a seventeenth embodiment of the present invention;

Fig. 49 is a block diagram of an electronic program
25 information receiving terminal including an electronic program

guide producing apparatus according to the seventeenth embodiment;

Fig. 50 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to an eighteenth embodiment of the present invention;

Fig. 51A shows an example of an electronic program table of main channel services;

Fig. 51B shows an example of an electronic program table of sub-channel services;

Fig. 52 shows an example of a service description table SDT of main channel services and sub-channel services, according to a nineteenth embodiment of the present invention;

Fig. 53 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to the nineteenth embodiment;

Fig. 54 shows an example of a service description table SDT of main channel services and sub-channel services, according to a twentieth embodiment of the present invention;

Fig. 55 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to the twentieth embodiment;

Fig. 56 shows an example of a service description table SDT

of main channel services and sub-channel services, according to a twenty-first embodiment of the present invention; and

Fig. 57 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to the twenty-first embodiment.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Preferred embodiments of an electronic program information preparing and transmitting apparatus and an electronic program guide producing apparatus according to the present invention are described with reference to the drawings.

(First Embodiment)

Fig. 2 is an explanatory view showing a total configuration of an electronic program information preparing and transmitting apparatus placed in a ^{central} ~~broadcasting station center~~ system according to a first embodiment of the present invention.

As shown in Fig. 2, an electronic program information preparing and transmitting apparatus 10 placed in a ^{central} ~~broadcasting station center~~ system comprises:

an electronic program information preparing unit 11, for preparing general electronic program information described on a general level from electronic program information of a channel service provided by ^{an individual} ~~a~~ broadcast service enterpriser ^{monitors}

for each of a plurality of broadcast service ~~enterprisers~~ ^{providers},
means for preparing individual electronic program information described
on an individual level from the electronic program information
of the channel service of ~~one~~ ^{each} broadcast service ~~enterpriser~~ ^{provider}
5 ~~for each broadcast service enterpriser~~, and ^{means for} preparing TS
specifying information indicating a transport stream for each
channel service;

an electronic program information outputting unit 12 for
outputting the pieces of general electronic program
10 information of the channel services prepared in the preparing
unit 11, the pieces of individual electronic program
information of the channel services prepared in the preparing
unit 11 and the pieces of TS specifying information prepared
in the preparing unit 11; and

15 an electronic program information multiplexing and
modulating unit 13 for multiplexing and modulating one piece
of individual electronic program information of a particular
channel service of a particular broadcast service ~~enterpriser~~ ^{provider}
and the pieces of general electronic program information of
20 ~~the~~ ^{other} broadcast service ~~enterprisers~~ ^{providers} of channel services other
than the particular channel service output from the outputting
unit 12 to produce packets of combined electronic program
information carried in a transport stream, which is indicated
by the TS specifying information of the particular broadcast
25 service ~~enterpriser~~ ^{provider}, for each piece of individual electronic

program information, and ^{means for} transmitting the packets of each piece of combined electronic program information to a plurality of viewer's terminals.

~~In the above configuration.~~ An operation performed in the
5 electronic program information preparing and transmitting
^{of the above configuration}
apparatus 10 ^A is described.

When each broadcast service ^{provider} ~~enterpriser~~ intends to provide electronic program information carried in a transport stream (TS) for a plurality of viewer's terminals, individual
10 electronic program information described on an individual
level corresponding to a high ~~detailed~~ ^{of detail} degree, is prepared in an electronic program information preparing unit 11 for each channel service (or each television channel) of television programs provided by ^{a specific} one broadcast service ^{provider} ~~enterpriser~~
15 according to both electronic program information detailed degree setting information I1 and ^{provider} ~~enterpriser~~ service correspondence information I2. The individual level corresponds to a high ~~detailed~~ ^{of detail} degree. Also, general electronic program information described on a general level is
20 prepared in an electronic program information preparing unit 11 for each channel service of television programs provided by ^{a corresponding} one broadcast service ^{provider} ~~enterpriser~~ according to the electronic program information detailed degree setting information I1 and the ^{provider} ~~enterpriser~~ service correspondence information I2. The
25 general level corresponds to a low ~~detailed~~ ^{of detail} degree. The

individual electronic program information described on the individual level and the general electronic program information described on the general level are prepared for each broadcast service ~~enterpriser~~ ^{provider}.

- 5 Electronic program information corresponding to one channel service of one or more television programs provided by one broadcast service ~~enterpriser~~ ^{provider} indicates guide (or attribute) information of the television programs and is carried in one transport stream. The electronic program information ~~detailed~~ ^{at detail} degree ^{of detail} setting information I1 indicates a detailed degree for contents of the individual electronic program information described on the individual level and a ~~detailed~~ ^{at detail} degree ^{of detail} for contents of the general electronic program information described on the general level. The ~~enterpriser~~ ^{provider} service
- 10 correspondence information I2 indicates the correspondence between each broadcast service ~~enterpriser~~ ^{provider} and one channel service carried in one transport stream, and the information I2 is included in ^{the} television program scheduling information I3. Each transport stream corresponds to one or more channel
- 15 services selected by each viewer.
- 20

In general, each broadcast service ~~enterpriser~~ ^{provider} desires to ^{cause} make a viewer ^{to} watch ^{the} detailed contents of ^{the} electronic program information of one or more television programs provided by ^{that} the broadcast service ~~enterpriser~~ ^{provider} when the viewer selects a

25 particular channel service (or a particular television

channel) of ^{that} the broadcast service ^{provider} enterpriser, and each
broadcast service ^{provider} enterpriser desires to ^{cause} make a viewer ^{to} watch ^{the}
brief contents of electronic program information of one or
more television programs provided by ^{that} the broadcast service
5 ^{provider} enterpriser when the viewer selects a channel service (or a
television channel) of another broadcast service ^{provider} enterpriser.

Therefore, in cases where ^{the} particular electronic program
information provided by a particular broadcast service
^{provider} enterpriser is carried in a particular transport stream
10 corresponding to the particular broadcast service ^{provider} enterpriser
and is transmitted to the viewer's terminals, the particular
electronic program information prepared on the individual
level is carried in a particular transport stream of the
particular broadcast service ^{provider} enterpriser and is transmitted to
15 the viewer's terminals. In contrast, in cases where ^{the} particular
electronic program information provided by a particular
broadcast service ^{provider} enterpriser is carried in ~~each of~~ transport
streams other than a particular transport stream of the
particular broadcast service ^{provider} enterpriser and is transmitted to
20 the viewer's terminals, the particular electronic program
information prepared on the general level is carried in each
of transport streams other than the particular transport
stream and is transmitted to the viewer's terminals.

In the electronic program information preparing unit 11, a
25 service description table (SDT) and an event information table

(EIT) are prepared as electronic program information corresponding to each channel service. The service description table SDT is prepared according to the ~~enterprise~~ ^{provider} service correspondence information I2, and the event information table
5 EIT is prepared according to the television program scheduling information I3 and the electronic program information ~~detailed~~ ^{of detail} degree ^A setting information I1.

In the electronic program information ~~detailed~~ ^{of detail} degree setting information I1, detailed contents of the electronic
10 program information described on the individual level and brief contents of the electronic program information described on the general level are set for each channel service. For example, in case of the electronic program information described on the individual level for a channel service ST100,
15 detailed guide information of a broadcast service ~~enterprise~~ ^{provider} is listed on the individual level in the service description table SDT corresponding to the channel service ST100 of the broadcast service ~~enterprise~~ ^{provider}, and detailed guide information of a plurality of television programs covering ~~over~~ ^{that} 7 days is
20 listed on the individual level in the event information table corresponding to the channel service ST100 of the broadcast service ~~enterprise~~ ^{provider}. The service description table and the event information table described on the individual level for the channel service ST100 are, for example, shown in Fig. 3.
25 Also, as the electronic program information described on the

general level for the channel service ST100, brief guide
information of the broadcast service ~~enterpriser~~ ^{provider} is listed on
the general level in the service description table SDT
corresponding to the channel service ST100 of the broadcast
5 service ~~enterpriser~~ ^{provider}, and brief guide information of a
plurality of television programs ^{broadcast} in one day is listed on the
individual level in the event information table corresponding
to the channel service ST100 of the broadcast service
~~enterpriser~~ ^{provider}. The service description table and the event
10 information table described on the general level for the
channel service ST100 are, for example, shown in Fig. 4.

In the same manner, the electronic program information of a
plurality of television programs covering over 14 days is
described on the individual level for a channel service ST101
15 of the television programs, and the electronic program
information of a plurality of television programs in one day
is described on the general level for the channel service
ST101.

In addition to the electronic program information, TS
20 specifying information, which indicates a particular transport
stream corresponding to the individual electronic program
information described on the individual level, is prepared
according to the ~~enterpriser~~ ^{provider} service correspondence
information I2 for each channel service. For example, as shown
25 in Fig. 2, because a comment "the channel service ST100 is

carried in a transport stream TS1 and the channel service ST101 is carried in a transport stream TS10" is described in the ~~enterpriser~~ ^{provider} service correspondence information I2, the TS specifying information indicates:

- 5 (1) the transport stream TS1 for the electronic program information which is described on the individual level for the channel service ST100,
- (2) transport streams other than the transport stream TS1 for the electronic program information which is described on the
- 10 general level for the channel service ST100,
- (3) the transport stream TS10 for the electronic program information which is described on the individual level for the channel service ST101, and
- (4) transport streams other than the transport stream TS10 for
- 15 the electronic program information which is described on the general level for the channel service ST101.

The pieces of individual electronic program information described on the individual level, the pieces of general electronic program information described on the general level

20 and the pieces of TS specifying information prepared in the electronic program information preparing unit 11 are sent to the electronic program information multiplexing and modulating unit 13 through the electronic program information outputting unit 12.

25 In the multiplexing and modulating unit 13, each piece of

individual electronic program information, which is described
on the individual level for a particular channel service of a
particular broadcast service ~~enterpriser~~ ^{provider}, is multiplexed with
pieces of general electronic program information described on
5 the general level for channel services of broadcast service
~~enterprisers~~ ^{providers} other than the particular broadcast service
~~enterpriser~~ ^{provider} and are carried in a particular transport stream
specified by TS specifying information corresponding to the
individual electronic program information described on the
10 individual level.

For example, in cases where the channel service ST100
corresponds to guide information of a plurality of first
television programs carried in the transport stream TS1 and in
cases where the channel service ST101 corresponds to guide
15 information of a plurality of second television programs
carried in the transport stream TS10, the electronic program
information (SDT and EIT described in detail) described on the
individual level for the channel service ST100 and the
electronic program information (SDT and EIT simply described)
20 described on the general level for the channel service ST101
are multiplexed with each other to be carried in the transport
stream TS1 corresponding to the first television programs and
are transmitted to the viewer's terminal, the electronic
program information (SDT and EIT described in detail)
25 described on the individual level for the channel service

ST101 and the electronic program information (SDT and EIT simply described) described on the general level for the channel service ST100 are multiplexed with each other to be carried in the transport stream TS10 corresponding to the second television programs and are transmitted to the viewer's terminal, and the electronic program information (SDT and EIT simply described) described on the general level for the channel services ST100 and ST101 are multiplexed with each other to be carried in each of transport streams, which correspond to other television programs, other than the transport streams TS1 and TS10, and are transmitted to the viewer's terminal.

Accordingly, because individual electronic program information corresponding to all channel services provided by all broadcast service ~~enterprisers~~ ^{providers} is not prepared, but individual electronic program information corresponding to one channel service of one television program provided by one broadcast service ~~enterpriser~~ ^{provider} is prepared, and carried in one transport stream, ~~a~~ ^{the} data transmission band required for each broadcast service ~~enterpriser~~ ^{provider} can be effectively used.

Also, detailed contents of the electronic program information corresponding to a channel service of one or more television programs provided by a particular broadcast service ~~enterpriser~~ ^{provider} are carried in a particular transport stream and can be transmitted to the viewer's terminals, and brief

contents of the electronic program information corresponding to the channel service of the television programs provided by the particular broadcast service ~~enterprise~~ ^{provider} are carried in each of transport streams other than the particular transport stream and are transmitted to the viewer's terminals.

Therefore, when the viewer selects a particular television channel corresponding to the particular transport stream of the particular broadcast service ~~enterprise~~ ^{provider}, the viewer can watch detail contents of the electronic program information of the television programs provided by the particular broadcast service ~~enterprise~~ ^{provider}. In contrast, when the viewer selects a television channel not corresponding to the particular transport stream of the particular broadcast service ~~enterprise~~ ^{provider}, the viewer watches brief contents of the electronic program information of the television programs provided by the particular broadcast service ~~enterprise~~ ^{provider}.

In this embodiment, each broadcast service ~~enterprise~~ ^{provider} provides ~~only~~ a group of television programs of ^{only} one channel service (or one television channel). However, ~~it is applicable~~ that each broadcast service ~~enterprise~~ ^{provider can} provide groups of television programs ^{for} of one or more channel services respectively carried in one transport stream. For example, in cases where a comment "a channel service ST100 of a broadcast service ~~enterprise~~ ^{provider} "Fujisan" is carried in a transport stream TS1, a channel service ST102 of the broadcast service

provider
enterpriser "Fujisan" is carried in a transport stream TS3 and
the channel service ST101 of a broadcast service *provider*
"Japan TV" is carried in a transport stream TS10" is described
in the *provider* enterpriser service correspondence information I2x;
5 (1) electronic program information (SDT and EIT described in
detail) described on the individual level for the channel
service ST100 is carried in each of the transport streams TS1
and TS3 of the broadcast service *provider* enterpriser "Fujisan",
(2) electronic program information (SDT and EIT simply
10 described) described on the general level for the channel
service ST100 is carried in each of transport streams other
than the transport streams TS1 and TS3,
(3) electronic program information (SDT and EIT described in
detail) described on the individual level for the channel
15 service ST101 is carried in the transport stream TS10 of the
broadcast service *provider* enterpriser "Japan TV",
(4) general electronic program information (SDT and EIT simply
described) described on the general level for the channel
service ST101 is carried in each of transport streams other
20 than the transport stream TS10,
(5) individual electronic program information (SDT and EIT
described in detail) described on the individual level for the
channel service ST102 is carried in each of the transport
streams TS1 and TS3 of the broadcast service *provider* enterpriser
25 "Fujisan", and

(6) general electronic program information (SDT and EIT simply described) described on the general level for the channel service ST102 is carried in each of transport streams other than the transport streams TS1 and TS3.

5 Accordingly, detailed^d contents of the electronic program information corresponding to a channel service of all television programs provided by a particular broadcast service ~~enterprise~~ *provider* can be carried in each of one or more particular transport streams of the particular broadcast service ~~enterprise~~ *provider* and can be transmitted to the viewer's terminals, 10 and brief contents of the electronic program information corresponding to the channel service of the television programs provided by the particular broadcast service ~~enterprise~~ *provider* are carried in each of transport streams other 15 than the particular transport streams of the particular broadcast service ~~enterprise~~ *provider* and are transmitted to the viewer's terminals .

Also, because brief contents of the general electronic program information corresponding to a plurality of channel 20 services of a plurality of broadcast service ~~enterprises~~ *providers*, other than a particular broadcast service ~~enterprise~~ *provider* can be obtained in each viewer's terminal, in cases where pieces of general electronic program information of the general level carried in transport streams of broadcast service ~~enterprises~~ *providers* 25 are gathered, a common electronic program guide of the

television programs provided by all broadcast service
~~enterprisers~~ ^{providers} can be produced in each viewer's terminal. For
example, as shown in Fig. 5, pieces of electronic program
information of the general level provided by broadcast service
5 enterprisers "Japan TV", "NHK", "TVS" and "Sun TV" are carried
in a transport stream of a ^{particular} broadcast service ~~enterpriser~~ ^{provider}
"Fujisan", pieces of electronic program information of the
general level provided by broadcast service ~~enterprisers~~ ^{providers}
"Fujisan", "NHK", "TVS" and "Sun TV" are carried in a
10 transport stream of ^{the} broadcast service ~~enterpriser~~ ^{provider} "Japan
TV", so that a common electronic program guide of the
television programs provided by all broadcast service
~~enterprisers~~ ^{providers} "Fujisan", "Japan TV", "NHK", "TVS" and "Sun TV"
can be produced from the pieces of electronic program
15 information of the general level provided by all broadcast
service ~~enterprisers~~ ^{providers} "Fujisan", "Japan TV", "NHK", "TVS" and
"Sun TV".

Also, because detailed contents of the electronic program
information corresponding to all channel services of a
20 particular broadcast service ~~enterpriser~~ ^{provider} can be obtained in
each viewer's terminal for each particular broadcast service
~~enterpriser~~ ^{provider}, an individual electronic program guide of the
television programs provided by one broadcast service
~~enterpriser~~ ^{provider} can be produced from the individual electronic
25 program information of the broadcast service ~~enterpriser~~ ^{provider}

described on the individual level in each viewer's terminal
for each broadcast service ~~enterpriser~~ ^{provider}. For example, as shown

in Fig. 6, when a viewer selects a television channel of the
broadcast service ~~enterpriser~~ ^{provider} "TVS", electronic program

5 information ^{at} of the individual level provided by the broadcast
service ~~enterpriser~~ ^{provider} "TVS" is received in the viewer's

terminal, an individual electronic program guide of the
television programs provided by the broadcast service

~~enterpriser~~ ^{provider} "TVS" can be produced from the electronic program

10 information of the individual level provided by the broadcast
service ~~enterpriser~~ ^{provider} "TVS".

Also, in this embodiment, the electronic program information
~~detailed degree~~ ^{of detail} setting information 11 sets detailed contents
of the electronic program information described on the

15 individual level and brief contents of the electronic program
information described on the general level for each channel

service. However, ~~it is applicable~~ that the television program
scheduling information 13 ^{can} set detailed contents of the

electronic program information described on ^{an} ~~the~~ individual

20 level and brief contents of the electronic program information
described on ^a ~~the~~ general level for each channel service.

(Second Embodiment)

In this embodiment, electronic program information is
prepared in a preparing unit for each broadcast service

25 ~~enterpriser~~ ^{provider}.

Fig. 7 is an explanatory view showing ^{the} ~~a~~ total configuration of an electronic program information preparing and transmitting apparatus placed in a ^{central} ~~a~~ broadcasting station center system according to a second embodiment of the present invention.

As shown in Fig. 7, an electronic program information preparing and transmitting apparatus 20 placed in a ^{central} ~~a~~ broadcasting station center system comprises the electronic program information preparing unit 11 and the electronic program information outputting unit 12 arranged for each broadcast service ^{provider} ~~enterpriser~~;

an electronic program information combining unit 21 for receiving the pieces of electronic program information and pieces of TS specifying information from the preparing units 11 of all broadcast service ^{providers} ~~enterprisers~~ and combining the electronic program information described on an individual level with one or more pieces of electronic program information described on general levels for each piece of electronic program information described on the individual level; and

an electronic program information multiplexing and modulating unit 22 for multiplexing and modulating each set of electronic program information described on an individual level and pieces of electronic program information described on general levels combined by the combining unit 21 to produce

packets of electronic program information carried in a transport stream indicated by the TS specifying information corresponding to the electronic program information described on the individual level and transmitting the packets to
5 viewer's terminals.

In the above configuration, an operation performed in the electronic program information preparing and transmitting apparatus 20 is described.

In each electronic program information preparing unit 11, a
10 service description table (SDT) and an event information table (EIT) corresponding to electronic program information described on an individual level are prepared for each channel service of one broadcast service ~~enterprise~~ ^{provider} according to electronic program information detailed degree setting
15 information 11 and television program scheduling information 13 of the broadcast service ~~enterprise~~ ^{provider}, independent of the preparation of other pieces of electronic program information performed in other electronic program information preparing units 11. In this case, ~~a~~ ^{the} ~~detailed~~ ^{of detail} degree, for the electronic
20 program information described on the individual level is determined by each broadcast service ~~enterprise~~ ^{provider}, so that the ~~detailed~~ ^{of detail} degree of the individual level is not fixed.

Also, a service description table (SDT) and an event information table (EIT) are prepared as an additional portion
25 of electronic program information described on a general level

for the channel service of the broadcast service ~~enterpriser~~ ^{provider}
in each electronic program information preparing unit 11
according to the electronic program information ~~detailed~~
degree, ^{f detail} setting information I1 and the television program

5 scheduling information I3 of the broadcast service
~~enterpriser~~ ^{provider}. In this case, ~~a detailed degree~~ ^{the} ~~for the~~ ^{f detail}
electronic program information described on the general level
is determined by each broadcast service ~~enterpriser~~ ^{provider}, so that
the ~~detailed~~ ^{f detail} degree of the general level is not fixed.

10 Also, TS specifying information indicating the transport
stream of the broadcast service ~~enterpriser~~ ^{provider} is prepared in
each electronic program information preparing unit 11. The
electronic program information described on an individual
level, the electronic program information described on a
15 general level and the TS specifying information prepared in
each electronic program information preparing unit 11 are sent
to the electronic program information combining unit 21
through the electronic program information outputting unit 12.

In the combining unit 21, enterpriser service
20 correspondence information I2, indicating the correspondence
between each broadcast service ~~enterpriser~~ ^{provider} and the channel
service, is recorded ^P and ~~a~~ particular electronic program
information, which is described on an individual level for the
channel service of a particular broadcast service ~~enterpriser~~ ^{provider},
25 is combined with one or more pieces of electronic program

information, which are described on general levels for the
channel services of one or more broadcast service ~~enterprisers~~ ^{providers}
other than the particular broadcast service ~~enterpriser~~ ^{provider},
according to the enterpriser service correspondence
5 information I2 for each particular broadcast service
~~enterpriser~~ ^{provider}.

Thereafter, each set of ~~the~~ electronic program information
described on an individual level and one or more pieces of
electronic program information described on ^a general level(s) is
10 sent with the TS, specifying information corresponding to the
electronic program information described on an individual
level, to the electronic program information multiplexing and
modulating unit 22. In the multiplexing and modulating unit
22, each set of ~~the~~ electronic program information described
15 on an individual level and one or more pieces of electronic
program information described on ^a general level(s) is multiplexed
and carried in a particular transport stream indicated by the
TS specifying information corresponding to the electronic
program information described on an individual level.

20 Accordingly, the electronic program information described
on an individual level, for a channel service of the particular
broadcast service ~~enterpriser~~ ^{provider}, can be carried with one or more
pieces of electronic program information described on general ^a
level(s) for channel services of broadcast service ~~enterprisers~~ ^{providers}
25 other than the particular broadcast service ~~enterpriser~~ ^{provider} in the

particular transport stream corresponding to television
programs provided by the particular broadcast service
provider ~~enterpriser~~ and the electronic program information described
on ~~the~~ ^{an} individual level and the electronic program information
5 described on the general levels are transmitted to viewer's
terminals in the same manner as in the first embodiment.

Also, because each broadcast service *provider* ~~enterpriser~~ can
prepare electronic program information independent of the
preparation of other pieces of electronic program information
10 performed by other broadcast service *providers* ~~enterprisers~~, even though
the preparation of the other pieces of electronic program
information is changed, each broadcast service *provider* ~~enterpriser~~ can
prepare electronic program information without any adverse
influence of the change ^{on} ~~in~~ the other pieces of electronic
15 program information of the other broadcast service
providers ~~enterprisers~~.

Also, because the ~~detailed~~ ^{of detail} degree ~~for~~ the electronic
program information prepared by each broadcast service
provider ~~enterpriser~~ is determined by the broadcast service
20 *provider* ~~enterpriser~~, each broadcast service *provider* ~~enterpriser~~ can
arbitrarily set the ~~detailed~~ ^{of detail} degree ~~for~~ electronic program
information described on an individual level and the ~~detailed~~
degree ^{of detail} ~~for~~ electronic program information described on ^a ~~the~~ general
level.

25 (Third Embodiment)

Contents of a part of electronic program information (or contents of common electronic program information) ^{are} ~~is~~ common to all broadcast service ~~enterprisers~~ ^{providers}. In this embodiment, the common electronic program information is not prepared by each broadcast service ~~enterpriser~~ ^{provider} but is prepared in a common preparing unit, and electronic program information (or non-common electronic program information), other than the common electronic program information, is prepared in the same manner as in the second embodiment.

10 Fig. 8 is an explanatory view showing a total configuration of an electronic program information preparing and transmitting apparatus ^{located} ~~placed~~ in a broadcasting station ~~center~~ ^{central} system according to ~~a~~ ^{the} third embodiment of the present invention.

15 As shown in Fig. 8, an electronic program information preparing and transmitting apparatus 30 ^{located} ~~placed~~ in a ~~center~~ ^{central} broadcasting station ~~center~~ system comprises:

a common electronic program information preparing unit 31 for preparing contents (called common electronic program information) common to the pieces of electronic program information of all broadcast service ~~enterprisers~~ ^{providers};

a common electronic program information outputting unit 32 for outputting the common electronic program information; ^{an} ~~the~~ electronic program information preparing unit 11 and ^{an} ~~the~~ electronic program information outputting unit 12,

arranged for each broadcast service ~~enterpriser~~ ^{provider}, for preparing non-common electronic program information described on an individual level and non-common electronic program information described on a general level from contents of the piece of

5 electronic program information other than the common electronic program information for each broadcast service ~~enterpriser~~ ^{means for} and ~~transmitting~~ ^{means for} the pieces of non-common electronic program information;

an electronic program information combining unit 33 for
10 receiving the non-common electronic program information and TS specifying information from each of the outputting units 12 of all broadcast service ~~enterprisers~~ ^{providers}, ~~receiving~~ ^{means for} the common electronic program information from the outputting unit 32 and
^{means for} combining the non-common electronic program information, which
15 is described on an individual level for a channel service of a particular broadcast service enterpriser, with one or more pieces of non-common electronic program information, which are described on general levels for channel services of broadcast service ~~enterprisers~~ ^{providers} other than the particular broadcast
20 service ~~enterpriser~~ ^{provider}, and the common electronic program information for each piece of non-common electronic program information described on an individual level; and

an electronic program information multiplexing and modulating unit 34 for multiplexing and modulating each set of
25 non-common electronic program information described on an

individual level, pieces of non-common electronic program information described on general levels and the common electronic program information combined with each other by the combining unit 33 to produce packets of electronic program information carried in a transport stream indicated by the TS specifying information corresponding to the non-common electronic program information described on the individual level and transmitting the packets to viewer's terminals.

In the above configuration, an operation performed in the electronic program information preparing and transmitting apparatus 30 is described.

Contents (called common electronic program information) common to the pieces of electronic program information of all broadcast service ~~enterprisers~~ ^{providers} is prepared in a common electronic program information preparing unit 31. For example, a network information table (NIT) and bouquet association table (BAT) are common to all broadcast service ~~enterprisers~~ ^{providers} because the NIT or BAT is hardly changed. In the NIT, tuning information used to select each of transport streams included in a network is described. In the BAT, names of channel services of all broadcast service ~~enterprisers~~ ^{providers}, names of all transport streams including the channel services and names of bouquets are described in a list. Each bouquet corresponds to one broadcast service ~~enterpriser~~ ^{provider}.

Also, contents (called non-common electronic program

information) of electronic program information other than the common electronic program information are prepared in the electronic program information preparing unit 11 of each broadcast service ~~enterpriser~~^{provider} in the same manner as in the
5 second embodiment.

Thereafter, the common electronic program information prepared in the unit 31 is sent to the electronic program information combining unit 33 through the common electronic program information outputting unit 32, and each piece of non-
10 common electronic program information is sent to the electronic program information combining unit 33 through the electronic program information outputting unit 12.

In the combining unit 33, the non-common electronic program information, which is described on an individual level for the
15 channel service of a particular broadcast service ~~enterpriser~~^{provider}, pieces of non-common electronic program information, which are described on general levels for channel services of broadcast service ~~enterprisers~~^{providers} other than the particular broadcast service ~~enterpriser~~^{provider}, and the common electronic program
20 information for each particular broadcast service ~~enterpriser~~^{provider}, are combined with each other. Thereafter, each set of the non-common electronic program information described on ~~the~~^{an} individual level, the pieces of non-common electronic program information described on ~~the~~ general levels and the common
25 electronic program information combined with each other is

multiplexed and modulated in the multiplexing and modulating unit 34 to produce packets of electronic program information, and the packets are carried in a particular transform stream, which is specified by the TS specifying information

5 corresponding to the non-common electronic program information described on the individual level and corresponds to one or more television programs provided by the particular broadcast service ~~enterpriser~~ ^{provider}, and are transmitted to the viewer's terminal.

10 Accordingly, because the common electronic program information common to all broadcast service ~~enterprisers~~ ^{providers} is not prepared in the electronic program information preparing unit 11 of each broadcast service ~~enterpriser~~ ^{provider} but is prepared in the common electronic program information preparing unit
15 31, the ~~preparation work of~~ ^{work for preparing} electronic program information performed by each broadcast service ~~enterpriser~~ ^{provider} can be reduced.

Also, in cases where a time and date table (TDT) is prepared by each broadcast service ~~enterpriser~~ ^{provider}, there is a
20 probability that a time set by one broadcast service ~~enterpriser~~ ^{provider} differs from a time set by another broadcast service ~~enterpriser~~ ^{provider}. Therefore, ~~it is applicable that the TDT~~ ^{should}
be prepared in the common electronic program information preparing unit 31 as ~~the~~ common electronic program
25 information.

(Fourth Embodiment)

In a digital broadcast system, video and audio signals indicating one or more television programs and a group of program specific information (PSI) tables prescribed according to the MPEG2 (or a group of service information (SI) tables prescribed according to digital video broadcasting (DVB) of European digital broadcast standards) are multiplexed and modulated to produce a digital broadcast signal for each broadcast service ~~enterpriser~~ ^{provider} (or for each bouquet). Each digital broadcast signal is composed of a plurality of packets, and each digital broadcast signal is carried in a transport stream and is transmitted to viewer's terminals. The PSI or SI is repeatedly transmitted to the viewer's terminals. When contents of the PSI or SI are renewed, a version number attached to the PSI or SI is incremented.

Fig. 9 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a fourth embodiment of the present invention.

As shown in Fig. 9, an electronic program information receiving terminal 40 comprises:

an antenna 41 for receiving a plurality of digital broadcast signals transmitted from the electronic program information preparing and transmitting apparatus 10, 20 or 30~~x~~
each digital broadcast signal ~~being~~ ^{is} carried in one transport

stream of one of a plurality of broadcast service

~~providers~~ ~~enterprisers~~ and audio and video signals of television programs provided by each broadcast service ~~enterpriser~~ ^{provider} are included in the digital broadcast signal;

5 an electronic program guide producing apparatus 42, for selecting one of the digital broadcast signals received ^{by} in the antenna 41, reproducing television programs from the selected digital broadcast signal and producing a common electronic program guide common to all broadcast service ~~enterprisers~~ ^{providers} and

10 an individual electronic program guide of each broadcast service ~~enterpriser~~ ^{provider} from the selected digital broadcast signal;

a remote control unit 43 for transmitting a remote control signal selected by a viewer to the electronic program guide
15 producing apparatus 42 to control the operation of the apparatus 42; and

a displaying unit 44, such as a television monitor, for displaying the television programs reproduced in the apparatus 42, displaying the common electronic program guide ^{at} any time
20 (refer to Fig. 5), and displaying the individual electronic program guide of one broadcast service enterpriser (refer to Fig. 6) when a television program of a channel service provided by the broadcast service ~~enterpriser~~ ^{provider} is displayed.

The electronic program guide producing apparatus 42
25 comprises:

a remote control signal receiving unit 51 for receiving the remote control signal transmitted from the remote control unit 43;

5 a tuner 52 for tuning the digital broadcast signals received by the antenna 41 according to the remote control signal to select a particular digital broadcast signal of a particular broadcast service enterpriser from the digital broadcast signals;

10 a demodulating unit 53 for demodulating the particular digital broadcast signal selected ^{by} ~~in~~ the tuner 52;

a demultiplexer 54 for demultiplexing the particular digital broadcast signal demodulated in the demodulating unit 53 to obtain video and audio signals, individual electronic program information of the particular broadcast service ~~enterpriser~~ ^{provider} and pieces of general electronic program information of broadcast service ~~enterpriser~~ ^{provider} other than the particular broadcast service ~~enterpriser~~ ^{provider} (a group of program specific information (PSI) tables or a group of service information (SI) tables) from the particular digital broadcast signal;

20 a section decoder 55 for decoding the PSI or SI of the electronic program information;

an electronic program information storing unit 56 for storing the pieces of general electronic program information and the individual electronic program information decoded in the section decoder 55 each time ^{a specific} ~~one~~ digital broadcast signal is

25

selected in the tuner 52;

an audio-video (A/V) signal decoder 57 for decoding the video and audio signals obtained in the demultiplexer 54 and outputting the decoded video and audio signals to the

5 displaying unit 44 to display one or more television programs; and

a central processing unit (CPU) 58 for controlling the remote control signal receiving unit 51, the tuner 52, the demodulating unit 53, the demultiplexer 54 and the section

10 decoder 55, controlling the audio-video signal decoder 57 to display a particular television program provided by ^a~~the~~ particular broadcast service ~~enterpriser~~ ^{provider} on the displaying unit 44, producing a common electronic program guide common to all broadcast service ~~enterprisers~~ ^{providers} from the pieces of general

15 electronic program information of the broadcast service ~~enterprisers~~ ^{providers} stored in the storing unit 56, producing an individual electronic program guide of the particular broadcast service ~~enterpriser~~ ^{provider} from the individual electronic program information of the particular broadcast service

20 ~~enterpriser~~ ^{provider} stored in the storing unit 56, controlling the audio-video signal decoder 57 to display an individual electronic program guide of the particular broadcast service ~~enterpriser~~ ^{provider} or the common electronic program guide on the displaying unit 44 according to the remote control signal

25 received in the receiving unit 51.

Therefore, the CPU 58 functions as a common electronic program guide producing means and an individual electronic program guide producing means.

In the above configuration, ~~the~~ ^{an} operation of the electronic
5 program guide producing apparatus 42 is described.

When a viewer selects a particular broadcasting station by operating a button of the remote control unit 43, a particular digital broadcast signal of the particular broadcasting station received in the antenna 41 is selected ~~in~~ ^{by} the tuner 52.
10 according to a remote control signal of the unit 43.

Thereafter, the particular digital broadcast signal is demodulated in the demodulating unit 53 and is demultiplexed in the demultiplexer 54, so that video and audio signals, individual electronic program information of the particular
15 broadcast service ~~enterpriser~~ ^{provider} and pieces of general electronic program information of broadcast service ~~enterpriser~~ ^{provider} other than the particular broadcast service ~~enterpriser~~ ^{provider} (a group of program specific information (PSI) tables or a group of service information (SI) tables), are obtained from the
20 particular digital broadcast signal. The video and audio signals are decoded in the audio-video signal decoder 57, and a plurality of television programs provided by the particular broadcast service enterpriser are displayed one after another on the displaying unit 44.

25 The tables PSI or SI of the electronic program information

(the pieces of general electronic program information and the individual electronic program information of the particular broadcast service ^{provider} ~~enterpriser~~ ^{are} ~~is~~ decoded in the section decoder 55 and ~~is~~ stored in the electronic program information storing unit 56. In this case, each table of the electronic program information has a packet identification number and/or a table identification number, and a packet identification number of one table is written in another table. Therefore, a plurality of packets corresponding to the electronic program information can be collected from a particular transport stream of the particular digital broadcast signal, and types of the tables can be specified according to the table identification numbers. Also, the tables (PSI or SI) of the electronic program information are repeatedly received in the apparatus 42, and a version number attached to each table is checked by the CPU 58. Therefore, updated tables such as a network information table (NIT), a service description table (SDT) and an event information table (EIT) can ~~be~~ always ~~be~~ stored in the storing unit 56.

20 For example, in ^{the} ~~a~~ case of ~~the~~ digital video broadcasting (DVB) of the European digital broadcast standards, the common electronic program information, such as a bouquet association table (BAT) and a network information table (NIT), is transmitted from the electronic program information preparing and transmitting apparatus 30 and is received in the

25

electronic program guide producing apparatus 42. As shown in Fig. 10, one or more transport streams corresponding to one network are listed in each NIT, and one or more channel services of the broadcasting station of one broadcast service enterpriser (or one bouquet) are listed in each BAT. In case of the MPEG2, as shown in Fig. 11, the common electronic program information, such as a program association table (PAT) and a program map table (PMT), is transmitted from the electronic program information preparing and transmitting apparatus 30 and is received in the electronic program guide producing apparatus 42.

Also, in case of the DVB, the non-common electronic program information, such as an event information table (EIT) and a service description table (SDT), is transmitted from the electronic program information preparing and transmitting apparatus 30 and is received in the electronic program guide producing apparatus 42. The word "event", prescribed according to the digital video broadcasting (DVB) of the European digital broadcast standards, denotes a television program. As shown in Fig. 12, information of one or more television programs of one channel service carried in one transport stream is described in each EIT, and one or more channel services of television programs carried in one transport stream are described in each SDT.

Therefore, in case of the DVB, as shown in Fig. 13, three

channel services of identification numbers ID1, ID2 and ID3 of
a broadcasting station Sb1, the BAT and NIT of the common
electronic program information and the SDT and EIT of the non-
common electronic program information corresponding to the
5 broadcasting station Sb1 are carried in a transport stream
TS20, three channel services of identification numbers ID4,
ID5 and ID6 of a broadcasting station Sb2, the BAT and NIT of
the common electronic program information and the SDT and EIT
of the non-common electronic program information corresponding
10 to the broadcasting station Sb2 are carried in a transport
stream TS30, and three channel services, of identification
numbers ID7, ID8 and ID9 of the broadcasting station Sb2, the
BAT and NIT of the common electronic program information and
the SDT and EIT of the non-common electronic program
15 information corresponding to the broadcasting station Sb2, are
carried in a transport stream TS40.

Thereafter, an individual electronic program guide, *made up of* one
or more television programs, is produced in the CPU 58 by using
the tables of the electronic program information stored in the
20 storing unit 56. In detail, the BAT is extracted from the
tables for each bouquet, a particular bouquet corresponding to
a particular television program currently viewed by the viewer
is specified, all particular channel services corresponding to
the particular bouquet are specified by using a particular BAT
25 of the particular bouquet, particular EIT and SDT

corresponding to the particular channel services are extracted from the tables, particular electronic program information corresponding to the particular channel services are extracted from the electronic program information, and an individual
5 electronic program guide is produced according to the particular EIT and SDT and the particular electronic program information. Thereafter, the individual electronic program guide of a particular broadcast service ~~enterpriser~~ ^{provider}, corresponding to the particular television program currently
10 watched by the viewer, is displayed on the displaying unit 44.

An example of the individual electronic program guide is shown in Fig. 14. The channel service identification numbers (ID) ST4 to ST9 are obtained from the particular SDT, and names of particular television programs, broadcast start times
15 of the particular television programs and broadcasting durations of the particular television programs are obtained from the particular EIT.

Accordingly, when a viewer watches a particular television program provided by a particular broadcast service
20 ~~enterpriser~~ ^{provider}, an individual electronic program guide of ~~the~~ ^{that} particular broadcast service ~~enterpriser~~ ^{provider} can be displayed.

Also, because an individual electronic program guide of a particular broadcast service ~~enterpriser~~ ^{provider}, corresponding to a particular television program currently watched by the viewer,
25 is displayed, there is no probability that an individual

electronic program guide of a broadcast service ^{provider} enterpriser,
^{that does} not corresponding to a particular television program currently
watched by the viewer is erroneously displayed, so that a
^{conflict} ^{individual} ~~trouble~~ between broadcast service ^{providers} enterprisers can be avoided.

5 In this embodiment, electronic program information is
transmitted from an electronic program information preparing
and transmitting apparatus to the electronic program guide
producing apparatus 42 according to a satellite communication
or a terrestrial television broadcasting service. However, ~~it~~
10 ~~is applicable that~~ ^{the} electronic program information ^{can} be
transmitted through another network system such as a telephone
circuit. Also, ~~it is applicable that~~ ^{the} electronic program
^{can be} information recorded in a recording medium such as a digital
versatile disc (DVD) or a floppy disc (FD).

15 (Fifth Embodiment)

Each broadcasting station (or each broadcast service
enterpriser) provides a plurality of television programs of a
plurality of channel services. That is, there are a plurality
of television channels corresponding to the channel services
20 for each broadcasting station.

In this embodiment, when a viewer selects a specific
bouquet (or a specific broadcasting station), a specific
channel service is selected from a plurality of channel
services of the specific broadcasting station, so that a
25 specific television channel corresponding to the specific

channel service is automatically selected.

Fig. 15 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a fifth embodiment of the present invention.

As shown in Fig. 15, an electronic program guide producing apparatus 59 comprises:

the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section decoder 55; the electronic program information storing unit 56; the audio-video signal decoder 57; and a central processing unit (CPU) 60 for controlling the remote control signal receiving unit 51, the demodulating unit 53, the demultiplexer 54 and the section decoder 55, controlling the audio-video signal decoder 57 to display a particular television program provided by the particular broadcast service ~~enterpriser~~ ^{provider} on the displaying unit 44, producing a common electronic program guide common to all broadcast service ~~enterprisers~~ ^{providers} from the pieces of general electronic program information of the ^{several} broadcast service ~~enterprisers~~ ^{providers} stored in the storing unit 56, producing an individual electronic program guide of the particular broadcast service enterpriser from the individual electronic program information of the particular broadcast service ~~enterpriser~~ ^{provider} stored in the storing unit 56, controlling the

audio-video signal decoder 57 to display an individual
electronic program guide of the particular broadcast service
provider enterpriser or the common electronic program guide on the
displaying unit 44 according to the remote control signal
5 received in the receiving unit 51, and controlling the tuner
52 to automatically select a specific television channel of a
specific broadcast service *provider* enterpriser in cases where a remote
control signal indicating the specific broadcast service
provider enterpriser is received in the remote control signal receiving
10 unit 51.

In the above configuration, ~~an~~ ^{the} operation of the electronic
program guide producing apparatus 59 is described with
reference to Fig. 16 and Fig. 17.

A bouquet association table (BAT), in which a default
15 selection flag is attached to each channel service, is
transmitted from the electronic program information preparing
and transmitting apparatus 10, 20 or 30 to the apparatus 59
for each broadcast service *provider* enterpriser, and the BATs are
stored in the storing unit 56 in the same manner as in the
20 fourth embodiment. For example, bouquet association tables of
the broadcasting stations Sb1 and Sb2 are shown in Fig. 16. As
shown in Fig. 16, because a default selection flag attached to
the channel service ST1 is set to "on" in the BAT of the
broadcasting station Sb1, the BAT indicates a preferential
25 selection of the channel service ST1.

Thereafter, when a viewer selects a particular broadcasting station by using the remote control unit 43, default selection flags of a particular bouquet association table (BAT) corresponding to the particular broadcasting station are checked by the CPU 60, and a particular television channel corresponding to a particular channel service, to which a default selection flag ^{that is} set to "on" is attached, is automatically selected. An example of a default selection is shown in Fig. 17.

As shown in Fig. 17, in cases where a viewer desires a broadcasting station "Japan TV" when the viewer watches a television program of a broadcasting station "Fujisan", the viewer pushes a button of the broadcasting station "Japan TV" arranged in the remote control unit 43. Thereafter, the CPU 60 checks the BAT of the broadcasting station "Japan TV", a channel service ST1 is specified because a default flag attached to the channel service ST1 is set to "on", and a television channel corresponding to the channel service ST1 is automatically selected.

Thereafter, television programs and electronic program information carried in a transport stream corresponding to the particular channel service is selected in the tuning unit 52. Therefore, a television program of the particular television channel can be automatically displayed on the displaying unit

44.

Accordingly, because each broadcast service ~~enterprise~~^{provider} can specify a particular television channel selected from a plurality of television channels of the broadcast service ~~enterprise~~^{provider}, the broadcast service ~~enterprise~~^{provider} can make the viewer^{to} automatically select the most important television channel^{as} determined by the broadcast service ~~enterprise~~^{provider}.

(Sixth Embodiment)

In this embodiment, a program attribute indicating an attribute of one television program is attached to an identification number of each television program in a table of the electronic program information.

Fig. 18 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a sixth embodiment of the present invention.

As shown in Fig. 18, an electronic program guide producing apparatus 61 comprises:

the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section decoder 55; the audio-video signal decoder 57;

an electronic program information storing unit 62 for storing the PSI or SI of the electronic program information decoded in the section decoder 55 and storing ~~a viewer~~^{an} attribute set by a viewer; and

a central processing unit (CPU) 63 for controlling the remote

control signal receiving unit 51, the tuner 52, the
demodulating unit 53, the demultiplexer 54 and the section
decoder 55, comparing the viewer^{identified} attribute, stored in the
storing unit 62, with a program attribute, which is attached to
5 an identification number of each television program
corresponding to the particular broadcast service^{provider} enterpriser
in a table of the electronic program information stored in the
storing unit 62, selecting a particular television program
corresponding to a particular program attribute matching with
10 the viewer attribute, controlling the audio-video signal
decoder 57 to display the particular television program on the
displaying unit 44, and controlling the electronic program
information storing unit 62 to display an individual
electronic program guide of the particular broadcast service
15 ^{provider} enterpriser on the displaying unit 44 by extracting particular
tables, corresponding to the particular broadcast service
^{provider} enterpriser, from the tables stored in the storing unit 62
according to the remote control signal received in the
receiving unit 51.

20 In the above configuration, a ^{an} ~~viewer~~ attribute set by a
viewer is stored in advance in the electronic program
information storing unit 62. The viewer attribute indicates ^{the} ~~a~~
taste of a viewer, features of the viewer and the like. When
the viewer selects a particular broadcast service^{provider} enterpriser
25 by using the remote control unit 43, a particular table, in

which identification numbers of a plurality of television programs provided by the particular broadcast service ~~enterpriser~~ ^{provider} are listed, is stored in the storing unit 62 in the same manner as in the fourth embodiment. In this case, a
5 program attribute indicating an attribute of one television program is attached to the identification number of each television program in the particular table.

Thereafter, a particular television program corresponding to a particular program attribute matching with the viewer
10 attribute is selected from the program attributes in the CPU 63, and the particular television program of a particular television channel is displayed on the displaying unit 44.

Accordingly, a particular program attribute matching with the viewer attribute can be selected, and a particular
15 television program corresponding to the particular program attribute can be automatically displayed. Therefore, the viewer can automatically select the particular television program suitable for a particular attribute of the viewer.

(Seventh Embodiment)

20 In this embodiment, a program service genre indicating ^{the} ~~a~~ genre of ^{a particular} ~~one~~ television program is attached to an identification number of each television program in a table of the electronic program information.

Fig. 19 is a block diagram of an electronic program
25 information receiving terminal, including an electronic program

guide producing apparatus, according to a seventh embodiment of the present invention.

As shown in Fig. 19, an electronic program guide producing apparatus 71 comprises:

5 the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section decoder 55; the audio-video signal decoder 57;

an electronic program information storing unit 72 for storing the PSI or SI of the electronic program information
10 decoded in the section decoder 55 and storing a viewer service genre set by a viewer; and

a central processing unit (CPU) 73 for controlling the remote control signal receiving unit 51, the tuner 52, the demodulating unit 53, the demultiplexer 54 and the section
15 decoder 55; comparing the viewer service genre stored in the storing unit 72 with a program service genre which is attached to an identification number of each television program corresponding to the particular broadcast service *provider* ~~enterpriser~~ in a table of the electronic program information stored in the
20 storing unit 72, selecting a particular television program corresponding to a particular program service genre agreeing with the viewer service genre, controlling the audio-video signal decoder 57 to display the particular television program on the displaying unit 44, and controlling the electronic
25 program information storing unit 72 to display an individual

electronic program guide of the particular broadcast service
provider
enterpriser on the displaying unit 44 by extracting particular
tables corresponding to the particular broadcast service
provider
enterpriser from the tables stored in the storing unit 72
5 according to the remote control signal received in the
receiving unit 51.

In the above configuration, a ~~viewer~~ service genre, which
is set by a viewer or is judged according to program viewing
records of the viewer, is stored in advance in the electronic
10 program information storing unit 72. The viewer service genre
indicates a service genre desired by a viewer. For example, a
movie genre, a sports genre, a music genre or the like is set
as the viewer service genre.

When the viewer selects a particular broadcast service
15 *provider* enterpriser by using the remote control unit 43, a particular
table, in which identification numbers of a plurality of
television programs provided by the particular broadcast
service *provider* enterpriser are listed, is stored in the storing unit
72 in the same manner as in the fourth embodiment. In this
20 case, a program service genre indicating a service genre of
one television program is attached to the identification
number of each television program in the particular table.

Thereafter, a particular television program corresponding
to a particular program service genre agreeing with the viewer
25 *identified*
service genre is selected from the program service genres in

the CPU 73, and ^a~~the~~ particular television program of a particular television channel ^{in that genre} is displayed on the displaying unit 44.

Accordingly, because a particular program service genre
5 agreeing with the viewer service genre can be selected and because a particular television program corresponding to the particular program service genre is displayed, the viewer can automatically select the particular television program belonging to a service genre suitable for the taste of the
10 viewer.

(Eighth Embodiment)

In cases where a high definition television (HDTV) program is transmitted from a ^{central} broadcasting station center system to ^{viewers'} ~~viewer's~~ terminals, because a transmission band of the HDTV
15 program is so wide as to extend over ^{the} ~~three~~ transmission bands of three standard television programs, the HDTV program, corresponding to three television channels of one transport stream, is transmitted after the three standard television programs corresponding to the three television channels are
20 transmitted. In this case, an event information table (EIT) of one channel service is prepared as a table of electronic program information in the ^{central} ~~broadcasting station center~~ system for each of the three television channels. Assuming that information of the HDTV program is described in each of the
25 three event information tables (EITs) corresponding to the

three television channels, the transmission band for the electronic program information cannot be efficiently used.

To prevent this problem in this embodiment, information of the HDTV program is described in one event information table (EIT), and event link information is written in the other two event information tables (EITs).

Fig. 20 shows three event information tables (EITs) prepared in the electronic program information preparing and transmitting apparatus 10, 20 or 30 according to an eighth embodiment of the present invention.

As shown in Fig. 20, in cases where three standard television programs identified by identification numbers TP35, TP51 and TP61 are transmitted from a ^{central} broadcasting station center system before ^{the} an HDTV program corresponding to ~~three~~ ~~television channels of the~~ three standard television programs is transmitted from the ^{central} broadcasting station center system, three particular event information tables (EITs) of channel services ST6, ST7 and ST8 are transmitted from the apparatus 10, 20 or 30. The HDTV program is identified by an identification number TP40 in the event information table (EIT) of the channel service ST6, the HDTV program is identified by an identification number TP52 in the event information table (EIT) of the channel service ST7, and the HDTV program is identified by an identification number TP62 in the event information table (EIT) of the channel service ST8.

In each particular event information table, a column of event link information is arranged. In the particular event information table (EIT) of the channel service ST6, information (for example, a title of the HDTV program, a
5 broadcasting start time of the HDTV program and a duration of broadcasting of the HDTV program) of the HDTV program is described in columns of the television program identification number TP40. Therefore, the television program TP40 is called an actual television program actually broadcasted.

10 In each of the particular event information tables (EITs) of the channel service ST7 and ST8, information of the HDTV program is not described, but event link information "refer to event TP40 of channel service ST6 of transport stream TS30" is described in the column of event link information. Therefore,
15 the television programs TP52 and TP62 are respectively called ~~a~~ virtual television programs not actually broadcasted.

Fig. 21 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to the eighth embodiment
20 of the present invention.

As shown in Fig. 21, an electronic program guide producing apparatus 81 comprises:

the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section
25 decoder 55; the electronic program information storing unit

56; the audio-video signal decoder 57; and

a central processing unit (CPU) 82 for controlling the remote control signal receiving unit 51, the tuner 52, the demodulating unit 53, the demultiplexer 54 and the section decoder 55, controlling the audio-video signal decoder 57 to display a particular television program of the particular broadcast service ~~enterpriser~~ *provider* on the displaying unit 44, controlling the electronic program information storing unit 56 to store electronic program information corresponding to each channel service, displaying an event information table on the displaying unit 44 in cases where event link information is attached to the event information table, and producing an individual electronic program guide of the particular broadcast service ~~enterpriser~~ *provider* while removing all virtual television programs from a broadcasting schedule of television programs of the particular broadcast service ~~enterpriser~~ *provider*.

In the above configuration, in cases where a particular event information table (EIT), in which event link information is described, is detected by the CPU 82 from the electronic program information stored in the storing unit 56, because a particular television program corresponding to the event link information is a virtual television program not actually broadcasted, the particular television program is removed from ~~the~~ *the* broadcasting schedule of television programs, and an individual electronic program guide of the particular

may be
broadcast service enterpriser is produced while using the
broadcasting schedule of television programs.

Also, the particular event information table (EIT) is
displayed on the displaying unit 44 to inform a viewer that a
5 television program corresponding to the event link information
is a virtual television program not actually broadcasted.

Also, in cases where the viewer specifies the virtual
television program, of which the identification number is
displayed, by using the remote control unit 43, an HDTV
10 program corresponding to the virtual television program is
displayed on the displaying unit 44.

Accordingly, even though an HDTV program is broadcasted,
because each virtual television program not actually
broadcasted can be specified by event link information,
15 information of the virtual television program can be
automatically removed from an individual electronic program
guide. Therefore, the viewer can watch the individual
electronic program guide in which information of the virtual
television program *has been* removed, and the data transmission band
20 for the electronic program information can be efficiently
used.

Also, in the same manner, information of the virtual
television program can be automatically removed from a common
electronic program guide.

25 In this embodiment, each virtual television program not

actually broadcasted is specified according to the event link information attached to the event information table (EIT). However, ~~it is applicable that~~ a table of television programs corresponding to the same HDTV program^{can} be prepared. In this case, each virtual television program can be specified according to the table.

(Ninth Embodiment)

In this embodiment, in cases where an HDTV program, extending over a plurality of television channels adjacent to each other, is broadcasted ~~to~~ in each viewer's terminal, a plurality of areas of the television channels are combined into a linked area in an electronic program guide (an individual electronic program guide or a common electronic program guide), and a guide of the HDTV program is described in the linked area of the electronic program guide.

Fig. 22 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a ninth embodiment of the present invention.

As shown in Fig. 22, an electronic program guide producing apparatus 91 comprises:

the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section decoder 55; the electronic program information storing unit 56; the audio-video signal decoder 57; and

a central processing unit (CPU) 92 for controlling the remote control signal receiving unit 51, the tuner 52, the demodulating unit 53, the demultiplexer 54 and the section decoder 55, controlling the audio-video signal decoder 57 to
5 display a particular television program of the particular broadcast service ~~enterpriser~~ ^{provider} on the displaying unit 44, controlling the electronic program information storing unit 56 to store electronic program information corresponding to each channel service, producing an electronic program guide, in
10 which information of an HDTV program extending over a plurality of television channels adjacent to each other is described in a linked area extending over guide areas of the television channels, in cases where event link information is described in one or more event information tables, and
15 displaying the electronic program guide on the displaying unit 44.

In the above configuration, in cases where one or more event information tables EIT (refer to Fig. 20), in which event link information is described, are detected in the CPU
20 92 because an HDTV program extending over three television channels adjacent to each other is broadcasted, an electronic program guide, in which a guide of the HDTV program is described in a linked area extending over guide areas of the television channels, is produced. For example, as shown in
25 Fig. 23, in cases where an HDTV program extending over three

television channels, CH6, CH7 and CH8, is broadcasted, a guide of the HDTV program is described in a linked area extending over guide areas of the television channels CH6, CH7 and CH8 in the electronic program guide. Thereafter, the electronic
5 program guide is displayed.

Accordingly, even though ^{the} data transmission band of an HDTV program extends over those ^{over which} of a plurality of standard television programs is ^{usually} broadcasted, because a guide ^{to} of the HDTV program is described in a linked area extending over
10 guide areas of a plurality of television channels ^{used for} of the standard television programs, the viewer can easily watch the electronic program guide.

In this embodiment, the event link information is described in one or more event information tables (EITs) to recognize
15 that one or more virtual television programs are the same as the HDTV program. However, ~~it is applicable that~~ a table of television programs corresponding to the same HDTV program ^{can} be prepared. In this case, each virtual television program can be specified according to the table.

20 (Tenth Embodiment)

In this embodiment, in cases where an HDTV program extending over a plurality of television channels is broadcasted, in each viewer's terminal, a guide ^{to} of the HDTV program is described in the guide area of each television
25 channel even though event link information is described in

each event information table (EIT) of channel services corresponding to the television channels, and the HDTV program guide described in each guide area is highlighted when a viewer selects one of the HDTV program guides displayed on the
5 displaying unit 44.

Fig. 24 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a tenth embodiment of the present invention.

10 As shown in Fig. 24, an electronic program guide producing apparatus 101 comprises:

the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section decoder 55; the electronic program information storing unit
15 56; the audio-video signal decoder 57; and

a central processing unit (CPU) 102 for controlling the remote control signal receiving unit 51, the tuner 52, the demodulating unit 53, the demultiplexer 54 and the section decoder 55, controlling the audio-video signal decoder 57 to
20 display a particular television program of the particular broadcast service *provider* enterpriser on the displaying unit 44, controlling the electronic program information storing unit 56 to store electronic program information corresponding to each channel service, producing an electronic program guide, in
25 which information of an HDTV program extending over a

plurality of television channels is described in a guide area of each television channel, in cases where event link information is described in one or more event information tables, displaying the electronic program guide on the displaying unit 44, and highlighting the HDTV program guide described in each guide area when a viewer selects one of the HDTV program guides displayed on the displaying unit 44.

In the above configuration, in cases where one or more event information tables EIT (refer to Fig. 20), in which event link information is described, are detected in the CPU 102, because an HDTV program extending over a plurality of television channels is broadcasted, an electronic program guide, in which guide information of the HDTV program is described in a guide area of each television channel, is produced and displayed. Thereafter, when a viewer selects one of the HDTV program guides displayed on the displaying unit 44 by using the remote control unit 43, all guides of the HDTV program described in the guide areas of the television channels are highlighted.

For example, as shown in Fig. 25, in cases where an HDTV program extending over three television channels, ^{for example} CH1, CH2 and CH4, is broadcasted, information of the HDTV program is described in each guide area of the television channels CH1, CH2 and CH4 in the electronic program guide. Thereafter, the electronic program guide is displayed. When a viewer selects

one HDTV program guide of one ^{of the} television channel^s CH1, CH2 or CH4, all HDTV program guides of the television channels CH1, CH2 and CH4 are highlighted.

Accordingly, because all HDTV program guides are
5 highlighted by selecting one HDTV program guide, the viewer can easily recognize all television channels corresponding to the HDTV program. In particular, even though the television channels corresponding to the HDTV program are separately positioned in the electronic program guide, the viewer can
10 quickly recognize all television channels corresponding to the HDTV program. Therefore, the viewer can easily watch the electronic program guide.

In this embodiment, the event link information is described in one or more event information tables (EITs) to recognize
15 that one or more virtual television programs are the same as the HDTV program. However, ~~it is applicable that~~ a table of television programs corresponding to the same HDTV program^{can} be prepared. In this case, each virtual television program can be specified according to the table.

20 (Eleventh Embodiment)

In this embodiment, a bandwidth in data transmission of one television program from a ^{central} broadcasting station center system to ^{the} receiving terminal apparatus of each viewer is described as bandwidth information for each television program in an
25 event information table (EIT) of electronic program information.

When the event information table (EIT) is received in each receiving terminal apparatus, information ^{about} ~~of~~ each television program is displayed on condition that ^{the} ~~a~~ display width of each television program information is proportional to the
5 bandwidth of the television program.

The transmission bandwidth is expressed by a data transfer rate (bits per second), so that the bandwidth information of each television program indicates ^{the} ~~a~~ display quality of the television program. An event information table (EIT) of the
10 channel service ST4 and an event information table (EIT) of the channel service (ST5) are shown in Fig. 26 as an example.

Fig. 27 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to an eleventh embodiment
15 of the present invention.

As shown in Fig. 27, an electronic program guide producing apparatus 111 comprises:

the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section
20 decoder 55; the electronic program information storing unit 56; the audio-video signal decoder 57; and

a central processing unit (CPU) 112 for controlling the remote control signal receiving unit 51, the tuner 52, the demodulating unit 53, the demultiplexer 54 and the section
25 decoder 55, controlling the audio-video signal decoder 57 to

display a particular television program of the particular
broadcast service ^{provider} ~~enterpriser~~ on the displaying unit 44,
controlling the electronic program information storing unit 56
to store electronic program information corresponding to each
5 channel service, producing an electronic program guide, in
which information of each television program is arranged on
condition that a display width of each television program
information is proportional to a bandwidth of the television
program, in cases where bandwidth information is described for
10 each television program of each event information table, and
displaying the electronic program guide on the displaying unit
44.

In the above configuration, in cases where an event
information table (EIT), in which bandwidth information
15 indicating a transmission bandwidth is described for each
television program, is received and stored in the storing unit
56 for each channel service, an electronic program guide, in
which information of each television program, having a display
width proportional to the transmission bandwidth of the
20 television program is displayed, is produced and is displayed.

For example, because bandwidth information indicating a
wide bandwidth of 18 Mbps is described for each of ^{the} television
programs "morning news" and "morning world" in the event
information tables (EIT) shown in Fig. 26, as shown in Fig. 28,
25 information ^{about} ~~of~~ each of ^{the} television programs "morning news" and

"morning world" in an electronic program guide has a wide display width.

Accordingly, when a viewer watches an electronic program guide, because a display width of information of each television program is proportional to the bandwidth of the television program, the viewer can visibly recognize ^{the} ~~a~~ display quality of the television program, so that the viewer can utilize the electronic program guide for the selection of one or more television programs.

10 In this embodiment, bandwidth information is described for each television program in the event information tables (EIT) of the electronic program information. However, it is applicable that bandwidth information be described for each channel service corresponding to one television channel in the service description table (SDT) of the electronic program
15 information. In this case, as shown in Fig. 29, an electronic program guide, in which ^{the} ~~a~~ display width for information ^{about} ~~of~~ a plurality of television programs corresponding to one television channel is set for each television channel, is
20 displayed, so that the viewer can visibly recognize ^{the} ~~a~~ display quality of television programs for each television channel. Also, ~~it is applicable that~~ bandwidth information ^{can} ~~be~~ included in the audio and video signals of each television program and the bandwidth information ^{can} ~~be~~ extracted from the audio and
25 video signals in the A/V decoder 57.

Also, in this embodiment, ^{the} a display quality of each television program is indicated by ^{the} a display width of information ^{about} of the television program. However, it is ^{appropriate} applicable that a colored mark or an icon indicating ^{the} a display quality of each television program be displayed according to the bandwidth information of the television program.

Also, in this embodiment, bandwidth information, indicating ^{the} a display quality of each television program, is transmitted from the ^{central} broadcasting station center system to each electronic program guide producing apparatus 111. However, ~~it is~~ ^{the} applicable that a channel service type of each television channel ^{should} be described in the service description tables (SDT) and a display width indicating ^{the} a display quality of each television program ^{should} be determined according to a correspondence table indicating the correspondence between each channel service type and one display width (refer to Fig. 30). The correspondence table indicating the correspondence between each channel service type and one display width is stored in advance in the storing unit 56 or is transmitted with the electronic program information. Therefore, when a channel service type of one television channel is received in the apparatus 111, a display width corresponding to the channel service type is determined in the CPU 113, and information of television programs corresponding to the television channel is displayed at the display width.

(Twelfth Embodiment)

In this embodiment, a three-dimensional electronic program guide (or a three-dimensional common electronic program guide) composed of a broadcast service *provider* enterpriser, a broadcasting
5 schedule and a television channel is displayed.

Fig. 31 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a twelfth embodiment of the present invention.

10 As shown in Fig. 31, an electronic program guide producing apparatus 121 comprises:

the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section decoder 55; the electronic program information storing unit
15 56; the audio-video signal decoder 57; and

a central processing unit (CPU) 122 for controlling the remote control signal receiving unit 51, the tuner 52, the demodulating unit 53, the demultiplexer 54 and the section decoder 55, controlling the audio-video signal decoder 57 to
20 display a particular television program of the particular broadcast service enterpriser on the displaying unit 44, controlling the electronic program information storing unit 56 to store electronic program information corresponding to each channel service, producing a three-dimensional electronic
25 program guide, in which information of each television program

is arranged in a three-dimensional area formed by a television channel axis, a broadcasting time axis and a broadcast service ~~enterpriser~~ ^{provider} axis on condition that a display width of each television program information in the television channel axis is proportional to a bandwidth of the television program, in cases where bandwidth information is described for each television program of each event information table, and displaying an oblique projective figure of the three-dimensional ~~at~~ electronic program guide on the displaying unit 44.

10 In the above configuration, in cases where an event information table (EIT), in which bandwidth information indicating a transmission bandwidth is described for each television program, is received and stored in the storing unit 56 for each channel service, a three-dimensional electronic program guide, in which information ^{about} ~~of~~ each television program is arranged in a three-dimensional area formed by a television channel axis, a broadcasting time axis and a broadcast service enterpriser axis, is produced on condition that a display width of each television program information in the television channel axis is proportional to a bandwidth of the television program. Thereafter, an oblique projective figure of the three-dimensional electronic program guide is displayed on the displaying unit 44.

25 An example of the three-dimensional electronic program guide is shown in Fig. 32. As shown in Fig. 32, ^{the} ~~a~~ television

channel ~~of~~ ^{for} each television program is expressed in an X direction, a broadcast service ~~enterpriser~~ ^{provider} of each television program is expressed in a Y direction, a broadcasting time of each television program is expressed in a Z direction, and a display width of each television program in the X direction is proportional to the bandwidth of the television program. Also, a promotion figure ~~of~~ ^{for} each television program, placed on the ~~most~~ ^{furthest} right side, is displayed on a Y-Z plane. The promotion figure is included in the electronic program information transmitted from the ~~broadcasting station center~~ ^{central} system and is displayed as an advertisement of broadcast service ~~enterpriser~~ ^{provider}.

Accordingly, the viewer can easily recognize ~~a~~ ^{the} broadcast service ~~enterpriser~~ ^{provider} of each television program by watching the three-dimensional electronic program guide. Also, the viewer can watch ~~a~~ ^{the} promotion figure ~~of~~ ^{for} each television program.

In this embodiment, the television channel of each television program is expressed in the X direction. However, the arrangement of the television channel, the broadcast service ~~enterpriser~~ ^{provider} and the broadcasting time is not limited to the three-dimensional electronic program guide shown in Fig. 32. For example, ~~it is applicable that~~ the broadcast service ~~enterpriser~~ ^{provider} of each television program ~~can~~ ^{also} be expressed in the X direction while ~~expressing~~ ^{the} a display width proportional to the bandwidth of each television program in the X

direction.

Also, ~~it is applicable that a television channel of~~ ^{the} ~~that is~~ ^{further} ~~placed on the most right side~~ ^{can} be changed to another television channel.

5 (Thirteenth Embodiment)

When the viewer desires to determine a particular television program, the viewer selects a plurality of television channels one after another to watch a plurality of television programs broadcasted ~~at~~ ^{//} at the same time one after
10 another while watching the electronic program guide of the television programs. In cases where an HDTV program extending over a plurality of television channels is broadcasted ~~in~~ ^{//} ~~to~~ each viewer's terminal, information ^{about} ~~of~~ the HDTV program is described in a plurality of guide areas of a plurality of
15 television channels ^{as} ~~in~~ the ninth and tenth embodiments.

Therefore, a television channel corresponding to the HDTV program is selected many times when the viewer desires to determine a particular television program.

For example, in cases where the electronic program guide
20 shown in Fig. 33 is displayed on the displaying unit 44, the viewer selects a plurality of television channels CH1 to CH5 one after another to watch a plurality of television programs TP100, TP105 and TP104 broadcasted in the same 4 o'clock ^{slot} ~~one~~ after another. In this case, when the viewer operates the
25 remote control unit 43 to move a cursor displayed on the

displaying unit 44 from the channel CH1 ^{on} of the left side to
the channel CH5 ^{on} of the right side, the channel CH1 (television
program TP100), the channel CH2 (HDTV program TP105), the
channel CH3 (HDTV program TP105), the channel CH4 (HDTV
5 program TP105) and the channel CH5 (television program TP104)
are selected in that order. Therefore, the HDTV program TP105
is displayed three times on the displaying unit 44.

In this embodiment, as shown in Fig. 34, the selection of
the television channels CH3 and CH4 is omitted, and the
10 channel CH1 (television program TP100), the channel CH2 (HDTV
program TP105) and the channel CH5 (television program TP104)
are selected in that order, and the television program TP100,
the television program TP105 and the television program TP104
are displayed on the displaying unit 44 in that order.

15 Fig. 35 is a block diagram of an electronic program
information receiving terminal including an electronic program
guide producing apparatus according to a thirteenth embodiment
of the present invention.

As shown in Fig. 35, an electronic program guide producing
20 apparatus 131 comprises:

the remote control signal receiving unit 51, the tuner 52;
the demodulating unit 53; the demultiplexer 54; the section
decoder 55; the electronic program information storing unit
56; the audio-video signal decoder 57; and
25 a central processing unit (CPU) 132 for controlling the

remote control signal receiving unit 51, the tuner 52, the
demodulating unit 53, the demultiplexer 54 and the section
decoder 55, controlling the audio-video signal decoder 57 to
display a particular television program of the particular
5 broadcast service *multiplier* on the displaying unit 44,
controlling the electronic program information storing unit 56
to store electronic program information corresponding to each
channel service, producing an electronic program guide, in
which information of an HDTV program extending over a
10 plurality of television channels adjacent to each other is
described in a linked area extending over guide areas of the
television channels, in cases where event link information is
described in one or more event information tables, displaying
the electronic program guide on the displaying unit 44,
15 selecting a plurality of television channels, which are
specified by a cursor moved on information of a plurality of
television programs in the electronic program guide, one after
another while selecting only one television channel from a
plurality of television channels corresponding to an HDTV
20 program, and displaying the television programs of the
selected television channels one after another.

In the above configuration, as shown in Fig. 33, even
though information *about* ~~of~~ an HDTV program extending over a
plurality of television channels is described in the guide
25 areas of the television channels, *the* ~~a~~ television channel

corresponding to the HDTV program is not selected in duplicate. Therefore, as shown in Fig. 34, the television channel CH2 is only selected from ^{among} the television channels CH2, CH3 and CH4 corresponding to the HDTV program TP105.

5 Accordingly, the viewer does not watch the HDTV program in duplicate, so that the viewer can efficiently determine ^{the} ~~a~~ television channel of a particular television program.

In this embodiment, an identification number such as TP100 is described as service identifying information of each
10 television program in the electronic program table. However, it is applicable that ^{the} ~~a~~ title of each television program or ^{the} ~~a~~ logotype of each television program ^{can} be described as service identifying information.

Also, information ^{about} ~~of~~ the HDTV program is described in the
15 linked area according to the ninth embodiment. However, ~~it is~~ ^{about} ~~applicable that~~ information ^{is} ~~of~~ the HDTV program extending over a plurality of television channels ^{the} ~~be~~ described in ~~a~~ guide area of each television channel according to the tenth embodiment.

20 (Fourteenth Embodiment)

In the thirteenth embodiment, as shown in Fig. 34, the numbers of the television channels are not displayed in serial order. Therefore, the viewer cannot easily realize the selection of the television channels.

25 In the fourteenth embodiment, in cases where an HDTV

program extending over a plurality of television channels is displayed on the displaying unit 44, as shown in Fig. 36, the numbers of all television channels corresponding to the HDTV program are displayed with the HDTV program.

5 Fig. 37 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a fourteenth embodiment of the present invention.

As shown in Fig. 37, an electronic program guide producing
10 apparatus 141 comprises:

the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section decoder 55; the electronic program information storing unit 56; the audio-video signal decoder 57; and

15 a central processing unit (CPU) 142 for controlling the remote control signal receiving unit 51, the tuner 52, the demodulating unit 53, the demultiplexer 54 and the section decoder 55, controlling the audio-video signal decoder 57 to display a particular television program of the particular
20 broadcast service *provider* ~~enterpriser~~ on the displaying unit 44, controlling the electronic program information storing unit 56 to store electronic program information corresponding to each channel service, producing an electronic program guide, in which information of an HDTV program extending over a
25 plurality of television channels adjacent to each other is

described in a linked area extending over guide areas of the television channels, in cases where event link information is described in one or more event information tables, displaying the electronic program guide on the displaying unit 44,
5 selecting a plurality of television channels, which are specified by a cursor moved on information of a plurality of television programs in the electronic program guide, one after another while selecting only a particular television channel from a plurality of television channels corresponding to an
10 HDTV program, and displaying the television programs of the selected television channels one after another with a channel number of each selected television channel on condition that a plurality of channel numbers of all television channels corresponding to the HDTV program are displayed with the HDTV
15 program when the particular television channel of the HDTV program is selected.

In the above configuration, as shown in Fig. 36, when the particular television channel (CH2) of the HDTV program is selected, channel numbers CH2, CH3 and CH4 of all television
20 channels corresponding to the HDTV program are displayed with the HDTV program. Therefore, all channel numbers CH1 to CH5 are displayed in serial order.

Accordingly, the viewer can easily ^{select} ~~realize~~ the ~~selection of~~ ^{desired} television channels.

25 In this embodiment, an identification number, such as TP100,

is described as ^{the} service identifying information ^{for} of each television program in the electronic program table. However, ~~it is applicable that~~ ^{the} a title of each television program or ~~the~~ logotype of each television program ^{can} be described as service
5 identifying information.

Also, information of the HDTV program is described in the linked area according to the ninth embodiment. However, ~~it is applicable that~~ ^{about} information ~~of~~ the HDTV program extending over a plurality of television channels ^{can} be described in ^{the} a guide
10 area of each television channel according to the tenth embodiment.

(Fifteenth Embodiment)

As shown in Fig. 38, a channel service ST101 of television programs belonging to a service type "SDTV", a channel service
15 ST103 of television programs belonging to a service type "music" and a group of channel services ST900, ST901, ST902 and ST903 of television programs belonging to the service type "music" are transmitted from the ^{central} broadcasting station ~~center~~ system to each electronic program information receiving
20 apparatus. The group of channel services ST900, ST901, ST902 and ST903 are subordinate to the channel service ST103.

As shown in Fig. 39, the television programs of the channel services ST101 and ST103 are carried in a transport stream TS3, and the television programs of the channel services
25 ST900, ST901, ST902 and ST903 are carried in a transport

stream TS5.

In this embodiment, because the channel services ST900, ST901, ST902 and ST903 are subordinate to the channel service ST103, as shown in Fig. 40, pieces of information ^{about} of the television programs of the channel services ST101 and ST103 are described in a service description table (SDT) of the transport stream (TS), and each of the channel services ST101 and ST103 is called a main channel service. Also, as shown in Fig. 41, pieces of information ^{about} of the television programs of the channel services ST101 and ST103 and pieces of information of the television programs of the channel services ST900, ST901, ST902 and ST903 are described in a service description table (SDT) of the transport streams TS3 and TS5. Each of the channel services ST900, ST901, ST902 and ST903 is called a sub-channel service. Also, pieces of information of the television programs of the channel service ST101 are described in an event information table (EIT) shown in Fig. 42, pieces of information of the television programs of the channel service ST103 are described in an event information table (EIT) shown in Fig. 43, and pieces of information of the television programs of the channel services ST900 to ST903 are respectively described in an event information table (EIT) shown in Fig. 44.

In the service description table (SDT) shown in Fig. 41, an identifier ^{such as} "main", is written in a main/sub column of each of the channel services ST101 and ST103 to classify each of the

channel services ST101 and ST103 as a main channel service. ~~A~~ ^{such as} identifier "sub" is written in a main/sub column of each of the channel services ST900, ST901, ST902 and ST903 to classify each of the channel services ST900, ST901, ST902 and ST903 as a sub-channel service. ~~reference~~ ^{Reference} ~~referential~~ service numbers "ST900 to ST903" are written in a referential service column of the channel service ST103 to indicate that the sub-channel services ST900 to ST903 are subordinate to the channel service ST103. ~~A~~ ^{reference} ~~referential~~ service number "ST103" is written in a ~~referential~~ ^{reference} service column of each of the channel services ST900, ST901, ST902 and ST903 to indicate that a main channel service of the sub-channel services ST900 to ST903 is the channel service ST103. ~~A~~ ^{reference} ~~referential~~ transport stream number "TS5" is written in a ~~referential~~ ^{reference} transport stream column of the channel service ST103 to indicate that sub-channel services subordinate to the channel service ST103 are carried in the transport stream TS5. ~~A~~ ^{reference} ~~referential~~ transport stream number "TS3" is written in a ~~referential~~ ^{reference} transport stream column of the transport stream TS5 to indicate that a main channel service of the sub-channel services ST900 to ST903 is carried in the transform stream TS3.

Therefore, the channel services ST101 and ST103 and a group of the channel services ST900, ST901, ST902 and ST903 are hierarchically described in the service description tables (SDT) and the event information tables (EIT).

Fig. 45 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a fifteenth embodiment of the present invention.

5 As shown in Fig. 45, an electronic program guide producing apparatus 151 comprises:

the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section decoder 55; the electronic program information storing unit
10 56; the audio-video signal decoder 57; and

a central processing unit (CPU) 152 for controlling the remote control signal receiving unit 51, the tuner 52, the demodulating unit 53, the demultiplexer 54 and the section decoder 55, controlling the audio-video signal decoder 57 to
15 display a particular television program of the particular broadcast service *provider* ~~enterpriser~~ on the displaying unit 44, controlling the electronic program information storing unit 56 to store electronic program information corresponding to each channel service, producing an electronic program guide, in
20 which pieces of information of a plurality of television programs are hierarchically described and arranged, in cases where a plurality of channel services are hierarchically described in a plurality of service description tables (SDT) and event information tables (EIT) of the electronic program
25 information stored in the storing unit 56, and displaying the

electronic program guide on the displaying unit 44.

In the above configuration, in cases where a plurality of channel services, hierarchically described in a plurality of service description tables (SDT) and event information tables
5 (EIT) of the electronic program information, are received from the ^{central} broadcasting station center system, an electronic program guide, in which pieces of information of a plurality of television programs are hierarchically described and arranged, is produced and displayed.

10 Accordingly, even though a large number of channel services are transmitted as pieces of electronic program information from the ^{central} broadcasting station center system to the electronic program guide producing apparatus 151 of each viewer, because the channel services are hierarchically classified into main
15 channel services and sub-channel services to classify information of television programs, the viewer can easily recognize pieces of information of a large number ^{about} ~~of~~ television programs hierarchically described in the electronic program guide (common electronic program guide or individual
20 electronic program guide), so that the viewer can easily select a particular broadcasting station or a particular television program.

In this embodiment, pieces of information of television programs are hierarchically described in the electronic
25 program guide. However, ~~it is applicable that~~ a plurality of

channel services^{can} be hierarchically described in the electronic program guide.

(Sixteen Embodiment)

In this embodiment, electronic program information,
5 corresponding to ~~the~~ main channel services, is carried in all transport streams (TS), and electronic program information, corresponding to each sub-channel service, is carried in a particular transport stream (TS) in which a plurality of television programs of the sub-channel service are
10 transmitted. The correspondence between each transport stream and a group of channel services is determined in advance in the ^{central} broadcasting station center system.

For example, as shown in Fig. 46, the service description table (SDT) shown in Fig. 40 and the event information tables
15 (EIT) shown in Fig. 42 and Fig. 43 are carried in all transport streams (TS) including the transport streams TS3 and TS5, and the service description table (SDT) shown in Fig. 41 and the event information tables (EIT) shown in Fig. 44 are carried in the transport stream TS5.

20 Fig. 47 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a sixteenth embodiment of the present invention.

As shown in Fig. 47, an electronic program guide producing
25 apparatus 161 comprises:

the remote control signal receiving unit 51, the tuner 52;
the demodulating unit 53; the demultiplexer 54; the section
decoder 55; the electronic program information storing unit
56; the audio-video signal decoder 57; and

5 a central processing unit (CPU) 162 for controlling the
remote control signal receiving unit 51, the tuner 52, the
demodulating unit 53, the demultiplexer 54 and the section
decoder 55, controlling the audio-video signal decoder 57 to
display a particular television program of the particular
10 broadcast service *provider* ~~enterpriser~~ on the displaying unit 44,
controlling the electronic program information storing unit 56
to store electronic program information corresponding to each
channel service, producing a common electronic program guide
according to the electronic program information corresponding
15 to main channel services carried in all transport streams,
producing an individual electronic program guide of the
particular broadcast service *provider* ~~enterpriser~~, in which pieces of
information of a plurality of television programs are
hierarchically described and arranged, according to the
20 electronic program information corresponding to sub-channel
services and main channel services carried in a particular
transport stream of the particular broadcast service
provider ~~enterpriser~~ in cases where a plurality of channel services are
hierarchically described in a plurality of service description
25 tables SDT and event information tables EIT of the electronic

program information stored in the storing unit 56, and displaying the common electronic program guide and the individual electronic program guide on the displaying unit 44.

In the above configuration, a common electronic program
5 guide is produced according to the electronic program information corresponding to main channel services carried in all transport streams. ~~An~~ ^A individual electronic program guide of the particular broadcast service ~~enterprise~~ ^{provider} is produced according to the electronic program information corresponding
10 to all sub-channel services and all main channel services carried in a particular transport stream of the particular broadcast service ~~enterprise~~ ^{provider} and the common electronic program guide and the individual electronic program guide are displayed.

15 For example, a common electronic program guide is produced according to the electronic program information of the channel services ST101 and ST103 carried in the transport stream TS3 and pieces of electronic program information corresponding to other main channel services, and an individual electronic
20 program guide is produced according to the electronic program information of the channel services ST101, ST103, ST900, ST901, ST902 and ST903 carried in the transport stream TS5.

Accordingly, a common electronic program guide and an individual electronic program guide can be easily produced and
25 displayed.

(Seventeenth Embodiment)

In this embodiment, a broadcast service ~~enterpriser~~ ^{provider} provides television programs of a plurality of channel services carried in a plurality of transport streams for each viewer, and a plurality of main channel services respectively have a group of sub-channel services. In this case, electronic program information corresponding to each group of sub-channel services of the broadcast service ~~enterpriser~~ ^{provider} is carried in each of all transport streams of the broadcast service ~~enterpriser~~ ^{provider}.

For example, as shown in Fig. 48, channel services ST101 and ST103 of television programs provided by a first broadcast service ~~enterpriser~~ ^{provider} are carried in a transport stream TS3~~x~~ ^A group of sub-channel services ST900, ST901, ST902 and ST903 subordinate to the channel service ST103 ^{are} is carried in a transport stream TS5~~x~~ ^A channel service ST105 of television programs provided by the first broadcast service ~~enterpriser~~ ^{provider} is carried in a transport stream TS6~~x~~ ^A group of sub-channel services ST910 and ST911 subordinate to the channel service ST105 ^{are} is carried in a transport stream TS7~~x~~ ^{and A} channel service ST106 of television programs, provided by a second broadcast service ~~enterpriser~~ ^{provider}, is carried in a transport stream TS7. In this case, ^{the} electronic program information corresponding to a first group of sub-channel services ST900, ST901, ST902 and ST903 is carried not only in the transport

stream TS5 but also in each of the transport streams TS3, TS6 and TS7, and electronic program information corresponding to a second group of sub-channel services ST910 and ST911 is carried not only in the transport stream TS7 but also in each of the transport streams TS3, TS5 and TS. The correspondence between each broadcast service *provider* and a group of channel services is determined in advance in the *central* broadcasting station center system.

Fig. 49 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a seventeenth embodiment of the present invention.

As shown in Fig. 49, an electronic program guide producing apparatus 171 comprises:

the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section decoder 55; the electronic program information storing unit 56; the audio-video signal decoder 57; and

a central processing unit (CPU) 172 for controlling the remote control signal receiving unit 51, the tuner 52, the demodulating unit 53, the demultiplexer 54 and the section decoder 55, controlling the audio-video signal decoder 57 to display a particular television program of the particular broadcast service *provider* on the displaying unit 44, controlling the electronic program information storing unit 56

to store electronic program information corresponding to each channel service, producing a common electronic program guide according to the electronic program information corresponding to main channel services carried in all transport streams, 5 producing an individual electronic program guide of the particular broadcast service *provider* ~~enterpriser~~, in which pieces of information of a plurality of television programs are hierarchically described and arranged, according to the electronic program information corresponding to all groups of 10 sub-channel services and all main channel services carried in one transport stream of the particular broadcast service *provider* ~~enterpriser~~ in cases where a plurality of channel services are hierarchically described in a plurality of service description tables SDT and event information tables EIT of the electronic 15 program information stored in the storing unit 56, and displaying the common electronic program guide and the individual electronic program guide on the displaying unit 44.

In the above configuration, electronic program information corresponding to all channel services of a particular 20 broadcast service *provider* ~~enterpriser~~ is carried in ~~each~~ of all of the transform streams of the particular broadcast service *provider* ~~enterpriser~~. When a viewer watches a particular television program carried in a particular transform stream of the particular broadcast service *provider* ~~enterpriser~~, because the 25 electronic program information corresponding to all channel

services of the particular broadcast service ~~enterprise~~ ^{provider} is carried in the particular transform stream, an individual electronic program guide of the particular broadcast service ~~enterprise~~ ^{provider} is produced according to the electronic program information corresponding to all channel services of the particular broadcast service ~~enterprise~~ ^{provider}. Therefore, the viewer can watch the individual electronic program guide displayed on the displaying unit 44.

Accordingly, the individual electronic program guide of the particular broadcast service ~~enterprise~~ ^{provider}, in which information corresponding to all groups of sub-channel services carried in one transport stream of the particular broadcast service ~~enterprise~~ ^{provider} is included, can be produced and displayed.

(Eighteenth Embodiment)

In this embodiment, in cases where a viewer selects a particular channel service (or a particular television channel) having a group of sub-channel services subordinate to the particular channel service, an electronic program guide of television programs corresponding to the group of sub-channel services is displayed.

Fig. 50 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to an eighteenth embodiment of the present invention.

As shown in Fig. 50, an electronic program guide producing

apparatus 181 comprises:

the remote control signal receiving unit 51, the tuner 52;
the demodulating unit 53; the demultiplexer 54; the section
decoder 55; the electronic program information storing unit
5 56; the audio-video signal decoder 57; and

a central processing unit (CPU) 182 for controlling the
remote control signal receiving unit 51, the tuner 52, the
demodulating unit 53, the demultiplexer 54 and the section
decoder 55, controlling the audio-video signal decoder 57 to
10 display a particular television program of the particular
broadcast service *provider* ~~enterpriser~~ on the displaying unit 44,
controlling the electronic program information storing unit 56
to store electronic program information corresponding to each
channel service, producing an electronic program guide, in
15 which pieces of information of television programs of a
plurality of main channel services are described, in cases
where one or more channel services are hierarchically
described in a plurality of service description tables (SDT) and
event information tables (EIT) of the electronic program
20 information stored in the storing unit 56, producing a
subordinate electronic program guide, in which pieces of
information of television programs of a group of sub-channel
services are described, displaying the electronic program
guide on the displaying unit 44, and displaying one
25 subordinate electronic program guide of a group of sub-channel

services subordinate to a particular main channel service in cases where the particular main channel service of the electronic program guide displayed is selected by a viewer.

In the above configuration, an electronic program guide,
5 in which pieces of information ~~of~~ ^{about} television programs of a plurality of main channel services are described, is produced. Also, a subordinate electronic program guide, in which pieces of information ~~of~~ ^{about} television programs of a group of sub-channel services subordinate to one main channel service are
10 described, is produced for each main channel service.

For example, channel services subordinate to each main channel service and a transport stream of the channel services are specified by referring identification numbers of
~~referential~~ ^{referenced} channels services and an identification number of
15 a ~~referential~~ ^{reference} transport stream described in the service description table shown in Fig. 40 or Fig. 41, and information of the group of sub-channel services subordinate to the main channel service is obtained from the event information table EIT shown in Fig. 44.

20 Thereafter, the electronic program guide is displayed on the displaying unit 44. An example of the electronic program guide is shown in Fig. 51A. When a viewer selects a particular channel service of the electronic program guide, a particular subordinate electronic program guide corresponding to the
25 particular channel service is automatically displayed on the

displaying unit 44. An example of the subordinate electronic program guide is shown in Fig. 51B. As shown in Fig. 51A, when a television channel CH33 is selected as a particular main channel service, information of television programs of a plurality of television channels CH50 to CH55 is displayed as a particular subordinate electronic program guide.

In cases where the particular main channel service has no sub-channel service, ~~no~~ any subordinate electronic program guide is ~~not~~ displayed.

10 Accordingly, even though there are a large number of channel services, because a plurality of electronic program guides of television programs of the channel services are hierarchically classified, the viewer can easily select an electronic program guide of desired television programs, so
15 that the viewer can easily specify a particular television program of a particular broadcast service ~~enterpriser~~ ^{provider}.

Also, even ~~if~~ ^{if} one or more channel services or television channels are added to an electronic program guide, the additional channel services or television channels can be
20 easily arranged in the electronic program guide.

In this embodiment, a channel service is selected by the viewer. However, ~~it is applicable that a television channel~~ ^{can} be directly selected.

(Nineteenth Embodiment)

25 In this embodiment, as shown in Fig. 52, a default sub-

channel service selecting flag is set for each sub-channel service in the service description table SDT, and the default sub-channel service selecting flag is set to "on" in one of the sub-channel services. Therefore, when a viewer selects the sub-channel services, a particular sub-channel service, in which a default sub-channel service selecting flag is set to "on", is automatically selected, and a particular television channel corresponding to the particular sub-channel service is selected.

10 Fig. 53 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a nineteenth embodiment of the present invention.

As shown in Fig. 53, an electronic program guide producing apparatus 191 comprises:

the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section decoder 55; the electronic program information storing unit 56; the audio-video signal decoder 57; and

20 a central processing unit (CPU) 192 for controlling the remote control signal receiving unit 51, the tuner 52, the demodulating unit 53, the demultiplexer 54 and the section decoder 55, controlling the electronic program information storing unit 56 to store electronic program information
25 corresponding to each channel service, producing an electronic

program guide, in which pieces of information of television programs of a plurality of main channel services are described, in cases where one or more channel services are hierarchically described in a plurality of service description tables (SDT) and event information tables (EIT) of the electronic program information stored in the storing unit 56 and a default sub-channel service selecting flag is set in the event information table (EIT) of sub-channel services for each sub-channel service, producing a subordinate electronic program guide, in which pieces of information of television programs of a group of sub-channel services are described, displaying the electronic program guide on the displaying unit 44, and controlling the audio-video signal decoder 57 to display a particular television program currently broadcasted in a particular sub-channel service on the displaying unit 44, on condition that a default sub-channel service selecting flag is set to "on" for the particular sub-channel service which is one of sub-channel services subordinate to a particular main channel service, in cases where the particular main channel service of the electronic program guide displayed is selected by a viewer.

In the above configuration, when the viewer selects a particular main channel service of the electronic program guide ^{to be} displayed, a plurality of sub-channel services, subordinate to the particular main channel service, is

specified, a particular sub-channel service, in which a default sub-channel service selecting flag is set to "on", is automatically selected from the sub-channel services, and a particular television program currently broadcast~~ed~~¹¹ in the particular sub-channel service is displayed on the displaying unit 44.

Accordingly, because each broadcast service ~~enterpriser~~^{provider} can specify a particular sub-channel service automatically selected, the broadcast service ~~enterpriser~~^{provider} can make the viewer select the most important sub-channel service determined by the broadcast service ~~enterpriser~~^{provider}. Therefore, an advertizement effect can be increased.

(Twentieth Embodiment)

In this embodiment, as shown in Fig. 54, a viewer attribute, such as ~~an~~^{the} age of the viewer or ~~a~~^{the} residential district of the viewer, is set for each sub-channel service in the service description table (SDT).

Fig. 55 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a twentieth embodiment of the present invention.

As shown in Fig. 55, an electronic program guide producing apparatus 201 comprises:

the remote control signal receiving unit 51, the tuner 52; the demodulating unit 53; the demultiplexer 54; the section

decoder 55; the electronic program information storing unit 56; the audio-video signal decoder 57; and

a central processing unit (CPU) 202 for controlling the remote control signal receiving unit 51, the tuner 52, the demodulating unit 53, the demultiplexer 54 and the section decoder 55, controlling the electronic program information storing unit 56 to store electronic program information corresponding to each channel service, producing an electronic program guide, in which pieces of information of television programs of a plurality of main channel services are described, in cases where one or more channel services are hierarchically described in a plurality of service description tables SDT and event information tables EIT of the electronic program information stored in the storing unit 56 and a viewer attribute is set in the event information table EIT of sub-channel services for each sub-channel service, producing a subordinate electronic program guide, in which pieces of information of television programs of a group of sub-channel services are described, displaying the electronic program guide on the displaying unit 44, and controlling the audio-video signal decoder 57 to display a particular television program currently broadcasted ^{11/01} in a particular sub-channel service on the displaying unit 44, on condition that a viewer attribute of the particular sub-channel service subordinate to a particular main channel service agrees with an attribute

input by the viewer, in cases where the particular main channel service of the electronic program guide displayed is selected by the viewer.

In the above configuration, as shown in Fig. 54, when the viewer selects ^athe main channel service ST103, a viewer attribute of each sub-channel service subordinate to the main channel service ST103^{is} ^dcompares with an attribute input by the viewer, and a particular sub-channel service, in which a viewer attribute agrees with the attribute input by the viewer, is automatically selected. For example, in cases where ^{the}an age of the viewer is 65 years old, a particular sub-channel service TS902 is selected. Thereafter, a particular television program currently broadcasted¹¹ in the particular sub-channel service is displayed on the displaying unit 44.

Accordingly, because one sub-channel service is automatically selected from a plurality of sub-channel services by inputting the attribute of the viewer, the viewer can easily select a sub-channel service suitable for the viewer without any ^{problem}~~troublesomeness~~.

Also, each broadcast service ^{provider}enterpriser can select a limited group of viewers from a large number of viewers to make the limited group of viewers watch television programs of a particular sub-channel service according to a common attribute of the limited group of viewers.

(Twenty-First Embodiment)

In this embodiment, as shown in Fig. 56, a genre, such as movie, sports or news, is set for each sub-channel service in the service description table (SDT). Also, a ~~viewer~~ genre suitable for the viewer is registered in advance in the *central* broadcasting station ~~center~~ system or is determined in the *central* broadcasting station ~~center~~ system according to television program viewing records of the viewer.

Fig. 57 is a block diagram of an electronic program information receiving terminal including an electronic program guide producing apparatus according to a twenty-first embodiment of the present invention.

As shown in Fig. 57, an electronic program guide producing apparatus 211 comprises:

the remote control signal receiving unit 51, the tuner 52; 15 the demodulating unit 53; the demultiplexer 54; the section decoder 55; the electronic program information storing unit 56; the audio-video signal decoder 57; and a central processing unit (CPU) 212 for controlling the remote control signal receiving unit 51, the tuner 52, the 20 demodulating unit 53, the demultiplexer 54 and the section decoder 55, controlling the electronic program information storing unit 56 to store electronic program information corresponding to each channel service, producing an electronic program guide, in which pieces of information of television 25 programs of a plurality of main channel services are

described, in cases where one or more channel services are hierarchically described in a plurality of service description tables SDT and event information tables EIT of the electronic program information stored in the storing unit 56 and a genre is set in the event information table EIT of sub-channel services for each sub-channel service, producing a subordinate electronic program guide, in which pieces of information of television programs of a group of sub-channel services are described, displaying the electronic program guide on the displaying unit 44, and controlling the audio-video signal decoder 57 to display a particular television program currently broadcasted in a particular sub-channel service on the displaying unit 44, on condition that a genre of the particular sub-channel service subordinate to a particular main channel service agrees with a viewer genre, in cases where the particular main channel service of the electronic program guide displayed is selected by the viewer.

In the above configuration, as shown in Fig. 56, when the viewer selects the main channel service ST103, a genre of each sub-channel service, subordinate to the main channel service ST103, ^{is compared} ~~compares~~ with a viewer ^{selected} ~~genre~~, and a particular sub-channel service, ^{having} ~~in which~~ a genre ^{that} ~~agrees~~ with the viewer ^{selected} genre, is automatically selected. For example, in cases where the viewer ^{has an} ~~takes~~ interest in a "movie" genre, a particular sub-channel service TS900 is selected. Thereafter, a

particular television program currently broadcast~~ed~~^{over} in the particular sub-channel service is displayed on the displaying unit 44.

Accordingly, because one sub-channel service is
5 automatically selected from a plurality of sub-channel services, the viewer can easily select a sub-channel service suitable for the viewer without any ~~troublesomeness~~^{problem}.

Having illustrated and described the principles of the present invention in a preferred embodiment thereof, it should
10 be readily apparent to those skilled in the art that the invention can be modified in arrangement and detail without departing from such principles. We claim all modifications coming within the scope of the accompanying claims.

WHAT IS CLAIMED IS:

1. An electronic program information preparing and transmitting apparatus, comprising:

electronic program information preparing means for
5 preparing general electronic program information, in which
electronic program information of a plurality of broadcast
service enterprisers is described on a general level, and
preparing individual electronic program information, in which
the electronic program information of one broadcast service
10 enterpriser is described on an individual level, for each
broadcast service enterpriser; and

electronic program information transmitting means for
transmitting the general electronic program information of the
broadcast service enterprisers and the individual electronic
15 program information of the broadcast service enterprisers
prepared by the electronic program information preparing
means.

2. An electronic program information preparing and
20 transmitting apparatus according to claim 1 in which the
general electronic program information and the individual
electronic program information corresponding to each
broadcast service enterpriser are prepared according to
electronic program information detailed degree setting
25 information which indicates a detailed degree of the

individual electronic program information described on the individual level and a detailed degree of the general electronic program information described on the general level.

5 3. An electronic program information preparing and transmitting apparatus according to claim 1 in which the general level corresponds to a low detailed degree, and the individual level corresponds to a high detailed degree.

10 4. An electronic program information preparing and transmitting apparatus according to claim 1 in which the electronic program information transmitting means comprises:

15 electronic program information outputting means for outputting the general electronic program information of the broadcast service enterprisers and the individual electronic program information of the broadcast service enterprisers prepared by the electronic program information preparing means; and

20 electronic program information multiplexing means for multiplexing the general electronic program information of the broadcast service enterprisers and one piece of individual electronic program information of one broadcast service enterpriser output by the electronic program information
25 outputting means to produce combined electronic program

information for each piece of individual electronic program information, and transmitting each piece of combined electronic program information to a viewer through a transmission line.

5

5. An electronic program information preparing and transmitting apparatus according to claim 1 in which transport stream specifying information indicating a transport stream is prepared by the electronic program information preparing means
10 for each piece of individual electronic program information of one broadcast service enterpriser, and the electronic program information transmitting means comprises:

electronic program information outputting means for
15 outputting the pieces of general electronic program information of the broadcast service enterprisers, the pieces of individual electronic program information of the broadcast service enterprisers and the pieces of transport stream specifying information prepared by the electronic program
20 information preparing means; and

electronic program information multiplexing means for multiplexing the pieces of general electronic program information of the broadcast service enterprisers and one piece of individual electronic program information of one
25 broadcast service enterpriser output by the electronic program

information outputting means to produce combined electronic program information for each piece of individual electronic program information, carrying each piece of combined electronic program information in a transport stream, which is
5 indicated by the piece of transport stream specifying information corresponding to the piece of individual electronic program information multiplexed in the piece of combined electronic program information, and transmitting the pieces of combined electronic program information carried in
10 the transport streams to the viewer.

6. An electronic program information preparing and transmitting apparatus according to claim 5 in which enterpriser service correspondence information, which
15 indicates the correspondence between each broadcast service enterpriser and a channel service carried in one transport stream is prepared by the electronic program information preparing means, and the transport stream specifying information is prepared according to the enterpriser service
20 correspondence information.

7. An electronic program information preparing and transmitting apparatus according to claim 6 in which one or more television programs provided by each broadcast service
25 enterpriser are carried in one transport stream of the

broadcast service enterpriser and are broadcasted on the viewer side, and the transport stream for carrying each piece of combined electronic program information, in which one piece of individual electronic program information corresponding to one broadcast service enterpriser is multiplexed, agrees with that of the broadcast service enterpriser.

8. An electronic program information preparing and transmitting apparatus according to claim 1 in which one piece of individual electronic program information of a particular broadcast service enterpriser and pieces of general electronic program information of broadcast service enterprisers other than the particular broadcast service enterpriser are transmitted to the viewer for each piece of individual electronic program information by the electronic program information transmitting means.

9. An electronic program information preparing and transmitting apparatus according to claim 1 in which the electronic program information preparing means comprises:

common electronic program information preparing means for preparing common electronic program information;

non-common electronic program information preparing means for preparing first non-common electronic program information not common to the broadcast service enterprisers on the

individual level from the electronic program information of one broadcast service enterpriser for each broadcast service enterpriser and preparing second non-common electronic program information not common to the broadcast service enterprisers
5 on the general level from the electronic program information of one broadcast service enterpriser for each broadcast service enterpriser, and the electronic program information transmitting means comprises:

10 electronic program information multiplexing means for multiplexing the common electronic program information prepared by the common electronic program information preparing means, one piece of first non-common electronic program information of a particular broadcast service
15 enterpriser prepared by the non-common electronic program information preparing means and pieces of second non-common electronic program information of broadcast service enterprisers other than the particular broadcast service enterpriser with each other to produce multiplexed electronic
20 program information for each particular broadcast service enterpriser; and

 multiplexed electronic program information transmitting means for transmitting the multiplexed electronic program information produced by the electronic program information
25 multiplexing means to the viewer for each particular broadcast

service enterpriser.

10. An electronic program information preparing and transmitting apparatus according to claim 9 in which transport stream specifying information indicating a transport stream is prepared by the non-common electronic program information preparing means for each broadcast service enterpriser, and the multiplexed electronic program information, in which one piece of first non-common electronic program information of one broadcast service enterpriser is multiplexed, is carried in the transport stream indicated by the transport stream specifying information corresponding to the broadcast service enterpriser.

11. An electronic program information preparing and transmitting apparatus according to claim 1 in which a plurality of channel services are listed in the general electronic program information or in the individual electronic program information of one broadcast service enterpriser prepared by the electronic program information preparing means, and service specifying information indicating the specifying of a particular channel service is arranged in the general electronic program information or the individual electronic program information of the broadcast service enterpriser to automatically select the particular channel

service from the channel services in cases where the broadcast service enterpriser is selected.

12. An electronic program information preparing and
5 transmitting apparatus according to claim 11 in which a viewer attribute is arranged in the general electronic program information or in the individual electronic program information as the service specifying information, a particular channel service, of which a viewer attribute agrees
10 with an attribute of the viewer, being selected from the channel services.

13. An electronic program information preparing and transmitting apparatus according to claim 11 in which a genre
15 is arranged in the general electronic program information or in the individual electronic program information as the service specifying information, a particular channel service, of which a genre agrees with a viewer favorite genre, being selected from the channel services.

20

14. An electronic program information preparing and transmitting apparatus according to claim 1 in which pieces of information of a plurality of television programs are described in the individual electronic program information or
25 the general electronic program information, and program link

describing information indicating that an actual television program actually broadcasted is the same as one or more virtual television programs not actually broadcasted is arranged in the individual electronic program information or
5 the general electronic program information.

15. An electronic program information preparing and transmitting apparatus according to claim 14 in which reference information for referring to information of an
10 actual television program actually broadcasted is added to information of one or more virtual television programs not actually broadcasted, and the reference information is transmitted.

15 16. An electronic program information preparing and transmitting apparatus according to claim 1 in which pieces of information of one or more television programs are listed in the general electronic program information or the individual electronic program information of each broadcast service
20 enterpriser prepared by the electronic program information preparing means, and a transmission bandwidth is described as the information of each television program.

17. An electronic program information preparing and
25 transmitting apparatus according to claim 16 in which

information indicating one broadcast service enterpriser,
information of a schedule and information of a television
channel are described as the information of each television
program on condition that a display width of each television
5 program is proportional to the transmission bandwidth of the
television program.

18. An electronic program information preparing and
transmitting apparatus according to claim 1 in which one or
10 more main channel services and one or more sub-channel
services subordinate to one main channel service are
hierarchically listed in the general electronic program
information or in the individual electronic program
information prepared by the electronic program information
15 preparing means.

19. An electronic program information preparing and
transmitting apparatus according to claim 1 in which one or
more main television programs and one or more sub-television
20 programs subordinate to one main television program are
hierarchically listed in the general electronic program
information or the individual electronic program information
prepared by the electronic program information preparing
means.

25

20. An electronic program information preparing and transmitting apparatus according to claim 1 in which one or more main television programs or main channel services and one or more sub-television programs or sub-channel services subordinate to one main television program or main channel service are hierarchically listed in the general electronic program information or the individual electronic program information prepared by the electronic program information preparing means, broadcasting times of the sub-television programs or sub-channel services subordinate to the main television program or main channel service are the same as each other, and the main television program or main channel service is not actually broadcasted.

21. An electronic program information preparing and transmitting apparatus according to claim 18 in which the general electronic program information including information of the main channel services is transmitted through all transmission lines, and the individual electronic program information including information of the sub-channel services is transmitted through a particular transmission line in which television programs of the sub-channel services are actually transmitted.

22. An electronic program information preparing and

transmitting apparatus according to claim 18 in which television programs provided by a particular broadcast service enterpriser are carried in a plurality of particular transmission lines, television programs of the sub-channel services are transmitted through one particular transmission line, the general electronic program information including information of the main channel services is transmitted through all transport streams, and the individual electronic program information including information of the sub-channel services is transmitted through each of the particular transmission lines.

23. An electronic program information preparing and transmitting apparatus according to claim 18 in which sub-channel service specifying information is arranged in the general electronic program information or in the individual electronic program information to specify a particular sub-channel service selected from the sub-channel services in cases where the main channel service of the sub-channel services is tuned by the viewer.

24. An electronic program information preparing and transmitting apparatus according to claim 18 in which a viewer attribute is arranged as information of each sub-channel service, a particular sub-channel service, of which the viewer

attribute agrees with an attribute of the viewer, being selected from the sub-channel services.

25. An electronic program information preparing and
5 transmitting apparatus according to claim 18 in which a genre is arranged as information of each sub-channel service, a particular sub-channel service, of which the genre agrees with a viewer favorite genre, being selected from the sub-channel services.

10

26. An electronic program information preparing and transmitting method, comprising the steps of:

preparing general electronic program information described on a general level from electronic program information of a
15 plurality of broadcast service enterprisers;

preparing individual electronic program information described on an individual level from the electronic program information of one broadcast service enterpriser for each broadcast service enterpriser; and

20 transmitting the general electronic program information of the broadcast service enterprisers and the individual electronic program information of the broadcast service enterprisers.

25 27. An electronic program information preparing and

transmitting method according to claim 26 in which the step of preparing individual electronic program information comprising the steps of:

5 preparing a plurality of information tables corresponding to a plurality of channel services as the individual electronic program information of each broadcast service enterpriser;

describing pieces of information of a plurality of television programs in each information table;

10 arranging program link describing information as the information of one television program for each information table to indicate that an actual television program actually broadcasted is the same as one or more virtual television programs not actually broadcasted.

15

28. An electronic program information preparing and transmitting method according to claim 26 in which the step of preparing individual electronic program information comprising the step of:

20 hierarchically listing one or more main channel services and one or more sub-channel services subordinate to one main channel service in the individual electronic program information.

25 29. An electronic program guide producing apparatus,

comprising:

electronic program information receiving means for receiving electronic program information of a plurality of broadcast service enterprisers;

5 common electronic program guide producing means for producing a common electronic program guide of channel services provided by the broadcast service enterprisers from the electronic program information of the broadcast service enterprisers received by the electronic program information
10 receiving means; and

individual electronic program guide producing means for producing an individual electronic program guide of channel services provided by one broadcast service enterpriser from the electronic program information of the broadcast service
15 enterpriser received by the electronic program information receiving means for each broadcast service enterpriser.

30. An electronic program guide producing apparatus according to claim 29; further comprising:

20 displaying means for displaying a television program of a channel service provided by a particular broadcast service enterpriser selected from the broadcast service enterprisers, displaying the common electronic program guide produced by the common electronic program guide producing means regardless of
25 the particular broadcast service enterpriser, and displaying a

particular individual electronic program guide of the
particular broadcast service enterpriser produced by the
individual electronic program guide producing means while
displaying the television program of the channel service
5 provided by the particular broadcast service enterpriser.

31. An electronic program guide producing apparatus according
to claim 30 in which a plurality of channel services are
listed in the electronic program information of one broadcast
10 service enterpriser received by the electronic program
information receiving means, service specifying information
indicating the specifying of a particular channel service
selected from the channel services is arranged in the
electronic program information, and a television program of
15 the particular channel service of the broadcast service
enterpriser is automatically displayed by the displaying means
in cases where the viewer selects the broadcast service
enterpriser.

20 32. An electronic program guide producing apparatus according
to claim 30 in which a plurality of channel services are
listed in one individual electronic program guide produced by
the individual electronic program guide producing means or in
the common electronic program guide produced by the common
25 electronic program guide producing means, a viewer attribute

is arranged as information of each channel service of the individual electronic program guide or the common electronic program guide, and a television program of a particular channel service of the broadcast service enterpriser is

5 automatically displayed by the displaying means in cases where the viewer attribute of the particular channel service agrees with an attribute of the viewer in the individual electronic program guide or the common electronic program guide.

10 33. An electronic program guide producing apparatus according to claim 30 in which a plurality of channel services are listed in one individual electronic program guide produced by the individual electronic program guide producing means or in the common electronic program guide produced by the common
15 electronic program guide producing means, a genre is arranged as information of each channel service of the individual electronic program guide or the common electronic program guide, and a television program of a particular channel service of the broadcast service enterpriser is automatically
20 displayed by the displaying means in cases where the genre of the particular channel service agrees with a viewer favorite genre in the individual electronic program guide or the common electronic program guide.

25 34. An electronic program guide producing apparatus according

to claim 30 in which pieces of information of a plurality of television programs are described in one individual electronic program guide produced by the individual electronic program guide producing means or in the common electronic program guide produced by the common electronic program guide producing means, program link describing information indicating that an actual television program actually broadcasted is the same as one or more virtual television programs not actually broadcasted is arranged in the individual electronic program guide or the common electronic program guide, and the individual electronic program guide or the common electronic program information is displayed by the displaying means.

35. An electronic program guide producing apparatus according to claim 30 in which information of a particular program extending over a plurality of television channels is described in one individual electronic program guide produced by the individual electronic program guide producing means or in the common electronic program guide produced by the common electronic program guide producing means, and the information of the particular program is displayed by the displaying means as the individual electronic program guide or the common electronic program guide.

36. An electronic program guide producing apparatus according to claim 30 in which information of a particular television program extending over a plurality of television channels is described in one individual electronic program guide produced by the individual electronic program guide producing means or the common electronic program guide produced by the common electronic program guide producing means, the information of the particular television program is described in each television channel of the individual electronic program guide or the common electronic program guide, the information of the particular television program described in each television channel is displayed by the displaying means as the individual electronic program guide or the common electronic program guide, and the selection of the particular television program is visually indicated in each television channel in cases where the particular television program of one television channel is selected.

37. An electronic program guide producing apparatus according to claim 30 in which display quality information is described as information of each television program in one individual electronic program guide produced by the individual electronic program guide producing means or in the common electronic program guide produced by the common electronic program guide producing means to indicate a display quality of the

television program, and pieces of information of the television programs are displayed by the displaying means as the individual electronic program guide or the common electronic program guide to indicate the display quality of each television program according to the display quality information of the television program.

38. An electronic program guide producing apparatus according to claim 30 in which information of one broadcast service enterpriser, information of a schedule and information of a television channel are described as information of each television program in one individual electronic program guide produced by the individual electronic program guide producing means or in the common electronic program guide produced by the common electronic program guide producing means, a transmission bandwidth is described as information of each television program in the individual electronic program guide or the common electronic program guide, and a three-dimensional electronic program guide composed of three components of the broadcast service enterpriser, the schedule and the television channel is displayed by the displaying means on condition that a display width of each television program in the three-dimensional electronic program guide is proportional to the transmission bandwidth of the television program.

39. An electronic program guide producing apparatus according to claim 30 in which information of television programs is described in one individual electronic program guide produced by the individual electronic program guide producing means or in the common electronic program guide produced by the common electronic program guide producing means, the information of the television programs is displayed by the displaying means as the individual electronic program guide or the common electronic program guide while displaying a television program of one television channel, and the electronic program guide producing apparatus, further comprises:

television channel changing means for changing a television program of a first television channel to a television program of a second television channel in cases where the television program of the first television channel has no relationship with the television program of the second television channel and changing the television program of the first television channel to a television program of a third television channel in cases where the television program of the first television channel refers to the information of the television program of the second television channel, the television program of the second television channel refers to the information of the television program of the first television channel or the television programs of the first and second television

channels refers to the information of a television program of one television channel.

40. An electronic program guide producing apparatus according
5 to claim 39 in which channel identifying information
indicating the second television channel or the third
television channel changed by the television channel changing
means and one or more fourth television channels is displayed
in cases where the second television channel or the third
10 television channel and the fourth television channels refer to
information of the same television channel, and channel
identifying information indicating the second television
channel or the third television channel changed by the
television channel changing means and one or more fifth
15 television channels is displayed in cases where the fifth
television channels refer to information of the second
television channel or information of the third television
channel.

20 41. An electronic program guide producing apparatus according
to claim 30 in which information of one or more main channel
services and information of one or more sub-channel services
subordinate to one main channel service are hierarchically
described in one individual electronic program guide produced
25 by the individual electronic program guide producing means or

described in one individual electronic program guide produced by the individual electronic program guide producing means or the common electronic program guide produced by the common electronic program guide producing means, the information of the main television programs is displayed by the displaying means as the individual electronic program guide, and the information of the sub-television programs is displayed by the displaying means as the individual electronic program guide or the common electronic program guide in cases where the main television program or a channel service of the main television program described in the information of the main television programs is selected.

44. An electronic program guide producing apparatus according to claim 30 in which information of a main television program and information of one or more sub-television programs subordinate to the main television program are hierarchically described in one individual electronic program guide produced by the individual electronic program guide producing means or the common electronic program guide produced by the common electronic program guide producing means, a viewer attribute is described as information of each sub-television program, and a particular sub-television program is automatically displayed by the displaying means, on condition that the viewer attribute described as the information of the

ABSTRACT

General electronic program information described on a general level and individual electronic program information described on an individual level are prepared according to
5 electronic program information of a channel service of a broadcast service *provider* ~~enterprise~~ for each channel service according to electronic program information ~~detailed~~ degree *of detail* setting information. The electronic program information ~~detailed~~ degree *of detail* setting information indicates a ~~detailed~~ degree *of detail* for contents of the individual electronic program
10 information described on ~~the~~ *an* individual level and a ~~detailed~~ degree *of detail* for contents of ~~the~~ *a* general electronic program information described on the general level. The general level corresponds to a low ~~detailed~~ degree *of detail*, and the individual level
15 corresponds to a high ~~detailed~~ degree *of detail*. One piece of individual electronic program information of a particular channel service and pieces of general electronic program information of channel services, other than the particular channel service, are multiplexed and transmitted to each viewer. Accordingly, the
20 general electronic program information and the individual electronic program information can be transmitted while effectively using a data transmission band.